





FEATURES	BENEFITS
<ul style="list-style-type: none"> Vented safety function Extremely high flow capacity Compact design Smaller outside dimension than comparable designs 	<ul style="list-style-type: none"> Easy to handle One hand operation Fully automatic operation Extremely energy efficient
SPECIFICATIONS	
Nominal flow diameter	7.5 mm (5/16")
Flow capacity	1950 l/min (68.8 CFM)*
Max. working pressure	16 bar (232 psi)
Min. burst pressure	140 bar (2030 psi)
Temperature range	-20°C to +100°C (-4°F to +212°F)
Coupling material	Zinc plated steel / brass
Coupling seal material	NBR
Nipple material	Hardened zinc plated steel
Connection force	86 N



Not actual size

Single Shut-off



Interchange

Asian Standard
Series 13

*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

NPT threads are available

eSAFE VENTED SAFETY COUPLINGS

315 SERIES
HOSE BARB

246

PART NUMBER	TUBE ID	METRIC EQ.
C103152002	1/4"	6.3 mm
C103152043	9/32"	7 mm
C103152004	3/8"	10 mm
C103152005	1/2"	13 mm

315 SERIES
STREAMLINE CONNECTION

246

PART NUMBER	TUBE OD	TUBE ID
C103152058	8.0 mm	5.0 mm
C103152060	10.0 mm	6.5 mm
C103152062	12.0 mm	8.0 mm
C103152063	13.0 mm	9.5 mm
C103152066	16.0 mm	11.0 mm

315 SERIES
BSPT MALE

246

PART NUMBER	THREAD
C103152152	1/4" BSPT
C103152154	3/8" BSPT
C103152155	1/2" BSPT

315 SERIES
STREAMLINE CONNECTION
WITH LOCK RING

246

PART NUMBER	TUBE OD	TUBE ID
C103152090	10.0 mm	6.5 mm
C103152092	12.0 mm	8.0 mm
C103152096	16.0 mm	11.0 mm

315 SERIES
BSPP FEMALE

246

PART NUMBER	THREAD
C103152202	1/4" BSPP
C103152204	3/8" BSPP

315 SERIES
SOFT-LINE CONNECTION

246

PART NUMBER	TUBE OD	TUBE ID
C103152082	12.0 mm	8.0 mm
C103152083	13.5 mm	9.5 mm
C103152085	16.0 mm	11.0 mm

315 SERIES
BSPP FEMALE
WITH LOCK RING

246

PART NUMBER	THREAD
C103152244	3/8" BSPP



Did you know?

Products with safety benefits are indicated by a chevron at the bottom of their table