

SPECIFICATIONS	Body Size				
	1/4"	3/8"	1/2"	3/4"	1"
Steel					
Max. working pressure	345 bar (5000 psi)	345 bar (5000 psi)	345 bar (5000 psi)	345 bar (5000 psi)	345 bar (5000 psi)
Flow rate	3 gpm	6 gpm	12 gpm	28 gpm	50 gpm
Spillage	0.006 ml	0.012 ml	0.020 ml	0.032 ml	0.035 ml
Stainless Steel					
Max. working pressure	300 bar (4351 psi)	250 bar (3626 psi)	250 bar (3626 psi)	200 bar (2901 psi)	150 bar (2176 psi)
Flow rate	3 gpm	6 gpm	12 gpm	20 gpm	27 gpm
Spillage	0.01 ml	0.02 ml	0.03 ml	0.04 ml	0.07 ml

FEATURES
• No spillage during connection
• Safety lock device
• No air inclusion during connection

Interchange
ISO 16028

Double Shut-Off

SPECIFICATIONS	Steel	316 Stainless Steel
Temperature range	-20°C to +120°C	-20°C to +200°C
Coupling & nipple material	Steel, zinc plated	316 stainless steel
Seal material	NBR	FKM

SAFETY

Did you know?

Products with safety benefits are indicated by a chevron at the bottom of their table

COUPLINGS - STEEL



ISO 16028
BSPP FEMALE

915

PART NUMBER	BODY SIZE	THREAD
M-FFC-14	1/4"	1/4" BSPP
M-FFC-38	3/8"	3/8" BSPP
M-FFC-38-12	3/8"	1/2" BSPP
M-FFC-12-12	1/2"	1/2" BSPP
M-FFC-12-34	1/2"	3/4" BSPP
M-FFC-34	3/4"	3/4" BSPP
M-FFC-34-1	3/4"	1" BSPP
M-FFC-1	1"	1" BSPP
M-FFC-1-114	1"	1 1/4" BSPP

NIPPLES - STEEL



ISO 16028
BSPP FEMALE

915

PART NUMBER	BODY SIZE	THREAD
M-FFN-14	1/4"	1/4" BSPP
M-FFN-38	3/8"	3/8" BSPP
M-FFN-38-12	3/8"	1/2" BSPP
M-FFN-12-12	1/2"	1/2" BSPP
M-FFN-12-34	1/2"	3/4" BSPP
M-FFN-34	3/4"	3/4" BSPP
M-FFN-34-1	3/4"	1" BSPP
M-FFN-1	1"	1" BSPP
M-FFN-1-114	1"	1 1/4" BSPP

COUPLINGS - 316 STAINLESS STEEL



ISO 16028
BSPP FEMALE

914

PART NUMBER	BODY SIZE	THREAD
B60-06F	1/4"	1/4" BSPP
B60-09F	3/8"	3/8" BSPP
B60-13F	1/2"	1/2" BSPP
B60-19F	3/4"	3/4" BSPP
B60-25F	1"	1" BSPP
B60-30F	1 1/4"	1 1/4" BSPP
B60-40F	1 1/2"	1 1/2" BSPP
B60-50F	2"	2" BSPP

NIPPLES - 316 STAINLESS STEEL



ISO 16028
BSPP FEMALE

914

PART NUMBER	BODY SIZE	THREAD
B60-06M	1/4"	1/4" BSPP
B60-09M	3/8"	3/8" BSPP
B60-13M	1/2"	1/2" BSPP
B60-19M	3/4"	3/4" BSPP
B60-25M	1"	1" BSPP
B60-30M	1 1/4"	1 1/4" BSPP
B60-40M	1 1/2"	1 1/2" BSPP
B60-50M	2"	2" BSPP

DUST CAPS FOR COUPLINGS



ISO 16028
DUST CAPS

915

PART NUMBER	SIZE
C921-FF-PDC-1/4F	1/4"
C921-FF-PDC-3/8F	3/8"
C921-FF-PDC-1/2F	1/2"
C921-FF-PDC-3/4F	3/4"
C921-FF-PDC-1F	1"

DUST CAPS FOR NIPPLES



ISO 16028
DUST CAPS

915

PART NUMBER	SIZE
C911-FF-PDC-1/4M	1/4"
C911-FF-PDC-3/8M	3/8"
C911-FF-PDC-1/2M	1/2"
C911-FF-PDC-3/4M	3/4"
C911-FF-PDC-1M	1"