

HQ SERIES

FEATURES

- Safety locking sleeve fitted as standard to prevent accidental disconnection
- Flat faces are easily wiped clean
- Allows for minimal inclusion of air & contaminants during connection
- Flat face design prevents fluid loss during disconnection
- Bi-directional flow

SPECIFICATIONS

Max. working pressure for body sizes:	1/4"	400 bar (5800 psi)
	3/8"	350 bar (5075 psi)
	1/2"	350 bar (5075 psi)
	3/4"	350 bar (5075 psi)
Operating temperature	-40°C to +106°C (-40°F to +223°F)	
Coupling & nipple material	Carbon steel with zinc nickel plating	
Seal material	NBR	

COUPLINGS – FEMALE HALF



HQ SERIES
BSPP FEMALE

8020

PART NUMBER	BODY SIZE	THREAD
HO-HQ06-F-04G	1/4"	1/4" BSPP
HO-HQ10-F-06G	3/8"	3/8" BSPP
HO-HQ10-F-08G	3/8"	1/2" BSPP
HO-HQ12-F-08G	1/2"	1/2" BSPP
HO-HQ12-F-12G	1/2"	3/4" BSPP
HO-HQ19-F-16G	3/4"	1" BSPP

NIPPLES – MALE HALF



HQ SERIES
BSPP FEMALE

8020

PART NUMBER	BODY SIZE	THREAD
HO-HQ06-M-04G	1/4"	1/4" BSPP
HO-HQ10-M-06G	3/8"	3/8" BSPP
HO-HQ10-M-08G	3/8"	1/2" BSPP
HO-HQ12-M-08G	1/2"	1/2" BSPP
HO-HQ12-M-12G	1/2"	3/4" BSPP
HO-HQ19-M-16G	3/4"	1" BSPP

HCP SERIES

FEATURES

- Designed to connect with the HQ series female half
- Flat faces are easily wiped clean
- Allows for minimal inclusion of air & contaminants during connection
- Flat face design prevents fluid loss during disconnection
- Bi-directional flow
- Connect under pressure with up to 350 bar locked in the male half
- Female half must have zero pressure when connecting male half under pressure

SPECIFICATIONS

Max. working pressure	350 bar (5075 psi)
Operating temperature	-40°C to +106°C (-40°F to +223°F)
Coupling & nipple material	Carbon steel with zinc nickel plating
Seal material	NBR

NIPPLES – MALE HALF



HCP SERIES
BSPP FEMALE

8020

PART NUMBER	BODY SIZE	THREAD
HO-HCP10-M-06G	3/8"	3/8" BSPP
HO-HCP10-M-08G	3/8"	1/2" BSPP
HO-HCP12-M-08G	1/2"	1/2" BSPP
HO-HCP12-M-12G	1/2"	3/4" BSPP
HO-HCP19-M-16G	3/4"	1" BSPP

Do you also need?



**Thread sealing
PTFE tape**

Find it on page 933, section fifteen