



FEATURES		BENEFITS	
<ul style="list-style-type: none"> Vented safety function Extremely high flow capacity Compact design Pre-applied sealant on male threads Smaller outside dimension than comparable designs 		<ul style="list-style-type: none"> Easy to handle One hand operation Fully automatic operation Extremely energy efficient 	
SPECIFICATIONS			
Nominal flow diameter	7.6 mm (5/16")		
Flow capacity	1800 l/min (63.5 CFM)*		
Max. working pressure	16 bar (232 psi)		
Min. burst pressure	140 bar (2030 psi)		
Connection force	86 N		
Temperature range	-20°C to +100°C (-4°F to +212°F)		
Coupling material	Hardened 316 stainless steel		
Coupling seal material	NBR		
Nipple material	316 stainless steel		



Not actual size



***High flow capacity**
 *Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

eSAFE VENTED SAFETY COUPLINGS

326 SERIES HOSE BARB



PART NUMBER	TUBE ID
C103262004	10 mm

326 SERIES BSPT MALE



PART NUMBER	THREAD
C103262152	1/4" BSPT
C103262154	3/8" BSPT
C103262155	1/2" BSPT

NPT MALE

C103262452	1/4" NPT
------------	----------

326 SERIES BSPP FEMALE



PART NUMBER	THREAD
C103262202	1/4" BSPP
C103262204	3/8" BSPP
C103262205	1/2" BSPP

NPT FEMALE

C103262402	1/4" NPT
------------	----------

326 SERIES STREAMLINE CONNECTION



PART NUMBER	TUBE OD	TUBE ID
C103262062	12.0 mm	8.0 mm

STANDARD NIPPLES

326 SERIES HOSE BARB – UNVALVED




PART NUMBER	TUBE ID	METRIC EQ.
C103265002	1/4"	6.3 mm
C103265003	5/16"	8 mm
C103265004	3/8"	10 mm

326 SERIES BSPT MALE – UNVALVED



PART NUMBER	THREAD
C103265152	1/4" BSPT
C103265154	3/8" BSPT

326 SERIES BSPP FEMALE – UNVALVED



PART NUMBER	THREAD
C103265204	3/8" BSPP
C103265205	1/2" BSPP

326 SERIES STREAMLINE CONNECTION UNVALVED



PART NUMBER	TUBE OD	TUBE ID
C103265062	12.0 mm	8.0 mm



Did you know?

Products with safety benefits are indicated by a chevron at the bottom of their table