

## SPECIFICATIONS

Max. working pressure	35 bar (508 psi)
Temperature range	-20°C to +100°C (-4°F to +212°F)
Coupling material	Nickel plated brass
Nipple material	Nickel plated brass

## Interchange

Series 20, Series 91,  
Series 06-003

## Single Shut-Off



## COUPLINGS

### CP20 SERIES HOSE BARB – VALVED



PART NUMBER	TUBE ID
CP20-1000	3 mm
CP20-HG04	4 mm
CP20-1001	5 mm

## NIPPLES

### CP20 SERIES HOSE BARB – UNVALVED



PART NUMBER	TUBE ID
CP20-5000	3 mm
CP20-HU04	4 mm
CP20-5001	5 mm

### CP20 SERIES METRIC MALE – VALVED



PART NUMBER	THREAD
CP20-EGM05	M5

### BSPP MALE – VALVED

CP20-1151	1/8" BSPP
-----------	-----------

### CP20 SERIES METRIC MALE – UNVALVED



PART NUMBER	THREAD
CP20-EUM05	M5

### BSPP MALE – UNVALVED

CP20-5151	1/8" BSPP
-----------	-----------

### CP20 SERIES METRIC FEMALE – VALVED



PART NUMBER	THREAD
CP20-DGM05	M5

### BSPP FEMALE – VALVED

CP20-1201	1/8" BSPP
-----------	-----------

### CP20 SERIES METRIC FEMALE – UNVALVED



PART NUMBER	THREAD
CP20-DUM05	M5

### BSPP FEMALE – UNVALVED

CP20-5201	1/8" BSPP
-----------	-----------

### CP20 SERIES HOSE COUPLINGS – VALVED



PART NUMBER	TUBE OD	TUBE ID
CP20-PG04	4 mm	3 mm
CP20-PG06	6 mm	4 mm

### CP20 SERIES HOSE NIPPLES – UNVALVED



PART NUMBER	TUBE OD	TUBE ID
CP20-PU04	4 mm	3 mm
CP20-PU05	5 mm	3 mm
CP20-PU06	6 mm	4 mm

### CP20 SERIES PANEL MOUNT HOSE COUPLINGS – VALVED



PART NUMBER	TUBE OD	TUBE ID	THREAD
CP20-SG04	4 mm	3 mm	M7 x 0.5
CP20-SG06	6 mm	4 mm	M8 x 0.8

Do you also need?

**PARKAIR®**

**Nylon tube**



Find it on pages 659 – 664, section ten