




FEATURES	BENEFITS
<ul style="list-style-type: none"> Extremely high flow capacity Compact design Vented safety function 	<ul style="list-style-type: none"> Fast, easy, one hand operation High performance Strong & durable for long life
SPECIFICATIONS	
Nominal flow diameter	10.4 mm (13/32")
Air flow	4000 l/min (141.2 CFM)
Max. working pressure	16 bar (232 psi)
Min. burst pressure	140 bar (2030 psi)
Temperature range	-20°C to +100°C (-4°F to +212°F)
Coupling material	Zinc plated steel / brass
Nipple material	Hardened zinc plated steel
Connection force	140 N

NPT threads are available



Single Shut-off
Interchange
CEJN Original, Eurostandard, Series 27

*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

eSAFE VENTED SAFETY COUPLINGS

410 SERIES
HOSE BARB



PART NUMBER	TUBE ID	METRIC EQ.
C104102003	5/16"	8 mm
C104102004	3/8"	10 mm
C104102005	1/2"	13 mm
C104102006	5/8"	16 mm
C104102007	3/4"	19 mm

410 SERIES
STREAMLINE CONNECTION



PART NUMBER	TUBE OD	TUBE ID
C104102066	16.0 mm	11.0 mm
C104102068	18.0 mm	13.0 mm
C104102071	21.0 mm	16.0 mm
C104102074	24.0 mm	19.0 mm

410 SERIES
BSPT MALE
WITH LOCTITE DRY-SEAL®



PART NUMBER	THREAD
C104102154	3/8" BSPT
C104102155	1/2" BSPT
C104102157	3/4" BSPT

410 SERIES
SOFT-LINE CONNECTION



PART NUMBER	TUBE OD	TUBE ID
C104102085	16.0 mm	11.0 mm
C104102088	18.0 mm	13.0 mm

410 SERIES
BSPP FEMALE



PART NUMBER	THREAD
C104102204	3/8" BSPP
C104102205	1/2" BSPP
C104102207	3/4" BSPP

Do you also need?

Blow guns

Find it on pages 726 – 731, section twelve

SAFETY Did you know?
Products with safety benefits are indicated by a chevron at the bottom of their table