

DOUBLE LOCK COUPLINGS

SPECIFICATION

Max. working pressure	10 bar (145 psi)
Temperature range	-40°C to +95°C (-40°F to +203°F)
Material	Plated iron

HOSE BARB
PLATED IRON



905

PART NUMBER	HOSE ID
AI-QDHE038M	3/8"
AI-QDHE050M	1/2"
AI-QDHE075M	3/4"
AI-QDHE100M	1"

BSPT MALE ADAPTOR
PLATED IRON



905

PART NUMBER	THREAD
AI-QDM038M	3/8" BSPT
AI-QDM050M	1/2" BSPT
AI-QDM075M	3/4" BSPT
AI-QDM100M	1" BSPT



HOSE BARB WITH COLLAR
PLATED IRON



905

PART NUMBER	HOSE ID
AI-QDHEC075	3/4"
AI-QDHEC100	1"

BSPP FEMALE ADAPTOR
PLATED IRON



905

PART NUMBER	THREAD
AI-QDF038M	3/8" BSPP
AI-QDF050M	1/2" BSPP
AI-QDF075M	3/4" BSPP
AI-QDF100M	1" BSPP

NBR SEAL
FOR DOUBLE LOCK FITTINGS



905

PART NUMBER	DESCRIPTION
AI-QDM4	NBR seal

MACDONALD COUPLINGS

FEATURES

- Bayonet couplings that eliminate the risk of accidental disconnection
- Ideal for applications where a robust fitting is required

SPECIFICATIONS

Max. working pressure for air	20 bar (300 psi)
-------------------------------	------------------

MALE HEAD
HOSE BARB



907

PART NUMBER	HOSE ID
AI-HM038S	3/8"
AI-HM050S	1/2"
AI-HM075S	3/4"

MALE HEAD
MALE THREAD



907

PART NUMBER	THREAD
AI-OM038S	3/8"
AI-OM050S	1/2"
AI-OM075S	3/4"
AI-OM100S	1"

MALE HEAD
FEMALE THREAD



907

PART NUMBER	THREAD
AI-IM038S	3/8"
AI-IM050S	1/2"
AI-IM075S	3/4"
AI-IM100S	1"

FEMALE HEAD
HOSE BARB



907

PART NUMBER	HOSE ID
AI-HF038S	3/8"
AI-HF050S	1/2"
AI-HF075S	3/4"
AI-HF100S	1"

FEMALE HEAD
MALE THREAD



907

PART NUMBER	THREAD
AI-OF038S	3/8"
AI-OF050S	1/2"
AI-OF075S	3/4"
AI-OF100S	1"

FEMALE HEAD
FEMALE THREAD



907

PART NUMBER	THREAD
AI-IF038S	3/8"
AI-IF050S	1/2"
AI-IF075S	3/4"
AI-IF100S	1"

