


FEATURES	BENEFITS
<ul style="list-style-type: none"> Extremely high flow capacity Compact design 	<ul style="list-style-type: none"> Fast, easy, one hand operation High performance Strong & durable for long life
SPECIFICATIONS	
Nominal flow diameter	10.4 mm (13/32")
Air flow	4000 l/min (141.2 CFM)
Max. working pressure	16 bar (232 psi)
Min. burst pressure	140 bar (2030 psi)
Temperature range	-20°C to +100°C (-4°F to +212°F)
Coupling material	Zinc plated steel / brass
Nipple material	Hardened zinc plated steel
Connection force	140 N

NPT threads are available



Not actual size

Single Shut-off
Interchange
CEJN Original, Eurostandard, Series 27

*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

STANDARD NIPPLES

410 SERIES HOSE BARB



255

PART NUMBER	TUBE ID	METRIC EQ.
C104105002	1/4"	6 mm
C104105003	5/16"	8 mm
C104105004	3/8"	10 mm
C104105005	1/2"	13 mm
C104105006	5/8"	16 mm
C104105007	3/4"	19 mm

410 SERIES BSPP FEMALE



255

PART NUMBER	THREAD
C104105202	1/4" BSPP
C104105204	3/8" BSPP
C104105205	1/2" BSPP
C104105207	3/4" BSPP

410 SERIES BSPT MALE WITH LOCTITE DRY-SEAL®



255

PART NUMBER	THREAD
C104105152	1/4" BSPT
C104105154	3/8" BSPT
C104105155	1/2" BSPT
C104105157	3/4" BSPT

410 SERIES STREAMLINE CONNECTION



255

PART NUMBER	TUBE OD	TUBE ID
C104105066	16.0 mm	11.0 mm
C104105068	18.0 mm	13.0 mm
C104105071	21.0 mm	16.0 mm
C104105074	24.0 mm	19.0 mm

Do you also need?



Pipe sealant



Find it on page 921, section fifteen