

SPECIFICATIONS	
Max. working pressure	12 bar (174 psi)
Temperature range	Up to 100°C (212°F)
MATERIALS	
Coupling	Malleable iron zinc plated & yellow passivated (free of chrome VI) or nylon
Seals	NBR



- Made of malleable iron zinc plated & yellow passivated (free of chrome VI) or nylon
- Reliable connections for aggressive, abrasive media
- Robust, reliable & durable
- Simple & fast handling
- Increased safety due to various safety systems
- Claw distance 58 mm unless otherwise stated





CLAW

DISTANCE

42 mm

58 mm

58 mm

58 mm

New





PART NUMBER	HOSE OD	HOSE ID	CLAW DISTANCE
CQP-3/4	32 mm	19 mm	58 mm
CQP-1	39 mm	25 mm	58 mm
CQP-2	48 mm	32 mm	58 mm



New

SANDBLAST COUPLINGS MALLEABLE IRON **FEMALE THREAD**

SANDBLAST COUPLINGS

HOSE OD

32 mm

39 mm

48 mm

54 mm

HOSE ID

19 mm

25 mm

32 mm

32 mm

MALLEABLE IRON

PART NUMBER

SS 19 T

SS 25 T

SS 32 T

SS 38 T



PART NUMBER	THREAD	LENGTH	
SK 38 TN	1 1/4"	62 mm	
SK 38 T	1 1/4"	55 mm	



SANDBLAST NOZZLE HOLDER NYLON **COARSE 50 FEMALE THREAD**




906

PART NUMBER	HOSE OD	HOSE ID	
NHP-3/4	32 mm	19 mm	
NHP-1	39 mm	25 mm	
NHP-2	32 mm	48 mm	

New

COUPLING SEAL







COUPLING SEAL NBR





PART NUMBER	FOR USE WITH
SDR-1	CQP-3/4
SDR-2	CQP-1
SDR-3	CQP-2



SCREW



	·· ==	
PART NUMBER	SIZE	
SHS	4.2 x 13	



AUTOMATIC SAFETY SYSTEM STEEL ZINC PLATED



PART NUMBER	SIZE	
DSR	Ø 2 wire	



SAFETY CLIP DIN 11024



