

SPECIFICATIONS

Max. working pressure	50 bar (725 psi)
Temperature range	-40°C to +90°C (-40°F to +194°F)
MATERIALS	
Coupling, handle	Malleable iron zinc plated & yellow passivate (free of chrome VI)
Hose stem	Steel zinc plated & yellow passivate (free of chrome VI)
Seals	NBR

FEATURES

- Made of malleable iron / steel zinc plated & yellow passivate (free of chrome VI)
- A turned stem profile can be offered for a perfect hose fit upon request, (drawing of hose or hose sample is required)
- To supply mortar, concrete or screed to pumps, spraying devices, plastering machines, etc.
- Other swivelling types available upon request
- Swivelling version made of three parts with Teflon™ slide to give a longer life expectancy



906

FEMALE MORTAR COUPLINGS RIGID, TWO HANDLE

PART NUMBER	THREAD
MIG 10-X25	1" BSPP
MIG 54/35	1 1/4" BSPP
MIG 20/50	2" BSPP



906

MORTAR PLUG BSPP MALE

PART NUMBER	THREAD
VAG 10-X25	1" BSPP
VAG 54/35	1 1/4" BSPP
VAG 20/50	2" BSPP



906

HOSETAIL MORTAR COUPLINGS RIGID, TWO HANDLE

PART NUMBER	HOSE OD	HOSE ID
MSTP-X25	39 mm	25 mm
MSTP 35	59 mm	35 mm
MSTP 50	68 mm	50 mm



906

MORTAR PLUG BSPP FEMALE

PART NUMBER	THREAD
VIG 10-X25	1" BSPP
VIG 54/35	1 1/4" BSPP
VIG 20/35	2" BSPP



906

MALE SCREWING STEM FOR HYDRAULIC CRIMPING BSPP MALE

PART NUMBER	THREAD	HOSE OD	HOSE ID
MSTP-X25T	1" BSPP	39 mm	25 mm
MSTP-35T	1 1/4" BSPP	59 mm	35 mm
MSTP-50T	2" BSPP	68 mm	50 mm



906

MORTAR PLUG HOSE BARB

PART NUMBER	HOSE OD	HOSE ID
VSTP-X25	39 mm	25 mm
VSTP 35	59 mm	35 mm
VSTP 50	68 mm	50 mm



906

COUPLING SEAL NBR

PART NUMBER	SIZE
MDR 25	1"
MDR 35	1 1/4"
MDR 50	2"



906

CRIMPED FERRULE FOR HYDRAULIC CRIMPING

PART NUMBER	HOSE OD	HOSE ID
PH-X25	39 mm	25 mm
PH-35	59 mm	35 mm
PH-50	68 mm	50 mm