

CLAW COUPLINGS WITH BORE FOR SAFETY CLIPS

SPECIFICATIONS

Max. working pressure	10 bar (145 psi)
Temperature range	-40°C to +95°C (-40°F to +203°F)
Coupling material	Malleable iron, zinc plated & yellow passivated (free of chrome VI)

FEATURES

- US-universal coupling, widely spread system for compressed air in construction & industry
- To be secured against accidental opening through safety clips DIN 11024
- With oil resistant rubber ring
- 100% couple test & sight control



906



906

HOSE US CLAW COUPLINGS WITH SAFETY COLLAR

PART NUMBER	HOSE ID
SKA 11*	3/8"
SKA 13	1/2"
SKA 19	3/4"
SKA 25	1"

*SKA 11: 2 parts with thread stem of steel

US MODY HOSE CLAW COUPLINGS WITH SAFETY COLLAR

PART NUMBER	HOSE ID
SSC 10	3/8"
SSC 13	1/2"
SSC 19	3/4"
SSC 25	1"



906

NPT MALE US CLAW COUPLINGS

PART NUMBER	THREAD
KAA 38	3/8" NPT
KAA 12	1/2" NPT
KAA 34	3/4" NPT
KAA 10	1" NPT



906

BLANK END US CLAW COUPLINGS

PART NUMBER	DESCRIPTION
UDM	Without chain



906

NPT FEMALE US CLAW COUPLINGS

PART NUMBER	THREAD
KIA 38	3/8" NPT
KIA 12	1/2" NPT
KIA 34	3/4" NPT
KIA 10	1" NPT



906

NBR SEAL SUITABLE FOR OIL / AIR

PART NUMBER	TEMPERATURE RANGE
GOOR	-40°C to +95°C

For Universal Clip – See page 170

WHIPCHECK

PARKAIR®

WHIPCHECK – A POSITIVE SAFEGUARD FOR HOSE CONNECTIONS

FEATURES

These strong steel cables help prevent hose whip in case of accidental separation of coupling or clamp device. The safety cable reaches across the hose fittings to provide stand by safety for the hose. Spring-loaded loops in the cable ends open easily to pass over the couplings for a firm grip on the hose. Thoroughly tested with years of proven service.

SPECIFICATIONS

Max. working pressure	13.8 bar (200 psi)
-----------------------	--------------------



910

WHIPCHECK SAFETY CABLE

PART NUMBER	CABLE	SIZE	APPROX. LENGTH
AH-WCK-1	1/8"	1/2" – 1 1/4"	22"
AH-WCK-2	1/4"	1 1/2" – 3"	39"
AH-WCK-3	3/8"	3" – 6"	1200 mm