

WATER PROFI CLAW COUPLINGS

SPECIFICATIONS

Max. working pressure	50 bar (725 psi)
Temperature range	Up to 95°C (203°F)
Body material	Forged brass MS 58
Seal material	NBR



906

FEATURES

- Easy to couple, high pressure & vacuum spectrum
- Maximum bore at optimum wall thickness
- Ergonomic formed claws – optimum safety against accidental opening
- Patented special rubber ring of NBR with optimum elasticity
- Universal coupling (interchangeable with types used worldwide) for water lines in industry, construction, garages, agriculture or civil installations



906

HOSE CLAW COUPLING

PART NUMBER	HOSE ID
GSK 10	3/8"
GSK 13	1/2"
GSK 16	5/8"
GSK 19	3/4"
GSK 25	1"
GSK 32	1 1/4"
GSK 38	1 1/2"

BSPP FEMALE CLAW COUPLING WITH THREAD SEALING RING

PART NUMBER	THREAD
GKI 14	1/4" BSPP
GKI 38	3/8" BSPP
GKI 12	1/2" BSPP
GKI 34	3/4" BSPP
GKI 10	1" BSPP
GKI 54	1 1/4" BSPP
GKI 15	1 1/2" BSPP

BSPP MALE CLAW COUPLING

PART NUMBER	THREAD
GKA 14	1/4" BSPP
GKA 38	3/8" BSPP
GKA 12	1/2" BSPP
GKA 34	3/4" BSPP
GKA 10	1" BSPP
GKA 54	1 1/4" BSPP
GKA 15	1 1/2" BSPP



906

BLANK END CLAW COUPLING

PART NUMBER	DESCRIPTION
GKO	Without chain



906

EPDM SEAL SUITABLE FOR WATER

PART NUMBER	TEMPERATURE RANGE
GKOR	-20°C to +95°C



906

ORIGINAL GEKA PLUS CLAW COUPLINGS – STAINLESS STEEL

SPECIFICATIONS

Max. working pressure	40 bar (580 psi)
Temperature range	-20°C to +200°C (-4°F to +392°F)
Body material	316 stainless steel
Seal material	FKM



906

FEATURES

- Easy to couple, high pressure & vacuum spectrum
- Maximum bore at optimum wall thickness
- Ergonomic formed claws – optimum safety against accidental opening
- Patented special rubber ring of FKM with optimum elasticity
- Universal coupling for applications in chemical, food or drink industry



906

HOSE CLAW COUPLING

PART NUMBER	HOSE ID
GSK 13 SS	1/2"
GSK 19 SS	3/4"
GSK 25 SS	1"

BSPP FEMALE CLAW COUPLING WITH THREAD SEALING RING

PART NUMBER	THREAD
GKI 12 SS	1/2" BSPP
GKI 34 SS	3/4" BSPP
GKI 10 SS	1" BSPP

BSPP MALE CLAW COUPLING

PART NUMBER	THREAD
GKA 12 SS	1/2" BSPP
GKA 34 SS	3/4" BSPP
GKA 10 SS	1" BSPP



906

BLANK END CLAW COUPLING

PART NUMBER	DESCRIPTION
GKO SS	Without chain



906

FKM SEAL CHEMICAL RESISTANT

PART NUMBER	TEMPERATURE RANGE
GKVR-N	-20°C to +200°C



906