

INTERPUMP 1SN

CONSTRUCTION


- Synthetic rubber tube
- One high tensile steel wire braid
- Synthetic rubber cover

APPLICATIONS

- Hydraulic oils, both mineral & biological
- Polyglycol based oils, water-oil emulsions & water

TEMPERATURE RANGE

Hydraulic oils: -40°C to +100°C (-40°F to +212°F)
Occasional peaks up to 125°C (257°F)
Polyglycol based oils, water-oil emulsions & water: up to 85°C (185°F)



New Additions

ONE WIRE BRAID HOSE



8080

PART NUMBER				
IP-TFD0012-04	1/4	13.4	225	900
IP-TFD0012-06	3/8	17.4	180	720
IP-TFD0012-08	1/2	20.6	160	640
IP-TFD0012-10	5/8	23.7	130	520
IP-TFD0012-12	3/4	27.7	105	420
IP-TFD0012-16	1	35.6	88	350

20 M COIL / LENGTH

IP-TFD0012-20	1 1/4	42.6	63	250
IP-TFD0012-24	1 1/2	49.6	50	200
IP-TFD0012-32	2	63.0	40	160

INTERPUMP 2SN

CONSTRUCTION


- Synthetic rubber tube
- Two high tensile steel wire braids
- Synthetic rubber cover, MSHA flame retardant approved

APPLICATIONS

- Hydraulic oils, both mineral & biological
- Polyglycol based oils, water-oil emulsions & water

TEMPERATURE RANGE

Hydraulic oils: -40°C to +100°C (-40°F to +212°F)
Occasional peaks up to 125°C (257°F)
Polyglycol based oils, water-oil emulsions & water: up to 85°C (185°F)



New Additions

TWO WIRE BRAID HOSE



8080

PART NUMBER				
IP-TFD0022-04	1/4	15.0	400	1600
IP-TFD0022-06	3/8	19.0	330	1320
IP-TFD0022-08	1/2	22.2	275	1100
IP-TFD0022-10	5/8	25.4	250	1000
IP-TFD0022-12	3/4	29.3	215	860
IP-TFD0022-16	1	38.1	165	660

20 M COIL / LENGTH

IP-TFD0022-20	1 1/4	46.5	125	500
IP-TFD0022-24	1 1/2	53.1	90	360
IP-TFD0022-32	2	65.8	80	320

INTERPUMP 2SC

CONSTRUCTION

- Synthetic rubber tube
- Two high tensile steel wire braids
- Synthetic rubber cover



APPLICATIONS

- Hydraulic oils, both mineral & biological
- Polyglycol based oils, water-oil emulsions & water

TEMPERATURE RANGE

Hydraulic oils: -40°C to +100°C (-40°F to +212°F)
Occasional peaks up to 125°C (257°F)
Polyglycol based oils, water-oil emulsions & water: up to 85°C (185°F)

TWO WIRE BRAID COMPACT HOSE



8080

PART NUMBER				
IP-TFA202K-04	1/4	13.3	400	1600
IP-TFA202K-06	3/8	17.1	330	1320
IP-TFA202K-08	1/2	20.0	275	1100
IP-TFA202K-12	3/4	27.6	215	860
IP-TFA202K-16	1	35.8	165	660

INTERPUMP 4SP

CONSTRUCTION

- Synthetic rubber tube
- Four high tensile steel wire spirals
- Synthetic rubber cover, MSHA flame retardant approved



APPLICATIONS


High pressure hydraulic system with extreme high pressure peaks for use with hydraulic oils, both mineral & biological, polyglycol based oils, water-oil emulsions & water

TEMPERATURE RANGE

Hydraulic oils: -40°C to +100°C (-40°F to +212°F)
Occasional peaks up to 125°C (257°F)
Polyglycol based oils, water-oil emulsions & water: up to 85°C (185°F)

New Additions

FOUR WIRE SPIRAL HOSE



8080

PART NUMBER				
IP-TFDM4SPN06	3/8	21.2	445	1780
IP-TFDM4SPN08	1/2	24.3	415	1660
IP-TFDM4SPN12	3/4	32.0	350	1400
IP-TFDM4SPN16	1	39.5	280	1120
IP-TFDM4SPN20	1 1/4	50.8	210	840