




FEATURES	BENEFITS
• Steel, lightweight construction	• Simple one hand operation
SPECIFICATIONS	
Nominal flow diameter	5.0 mm (3/16")
Flow capacity	870 l/min (30.7 CFM)*
Max. working pressure	35 bar (508 psi)
Temperature range	-20°C to +100°C (-4°F to +212°F)
MATERIALS	
Coupling body	Nickel plated steel
Coupling back part	Nickel plated brass
Sleeve	Nickel plated steel
Valve	Brass
Springs, locking O-ring & balls	Stainless steel
Seals	NBR
Nipple	Nickel plated steel

Interchange
Series 17



*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

COUPLINGS

NIPPLES

CP17 SERIES HOSE BARB



PART NUMBER	TUBE ID	METRIC EQ.
CP17-1002	1/4"	6 mm
CP17-1003	5/16"	8 mm
CP17-1004	3/8"	10 mm
CP17-1005	1/2"	13 mm

CP17 SERIES HOSE BARB



PART NUMBER	TUBE ID	METRIC EQ.
CP17-5002	1/4"	6 mm
CP17-5003	5/16"	8 mm
CP17-5004	3/8"	10 mm

CP17 SERIES BSPT MALE



PART NUMBER	THREAD
CP17-1152	1/4" BSPT
CP17-1154	3/8" BSPT
CP17-1155	1/2" BSPT

CP17 SERIES BSPT MALE



PART NUMBER	THREAD
CP17-5152	1/4" BSPT
CP17-5154	3/8" BSPT

CP17 SERIES BSPP FEMALE



PART NUMBER	THREAD
CP17-1202	1/4" BSPP
CP17-1204	3/8" BSPP
CP17-1205	1/2" BSPP

CP17 SERIES BSPP FEMALE



PART NUMBER	THREAD
CP17-5202	1/4" BSPP
CP17-5204	3/8" BSPP
CP17-5205	1/2" BSPP

CP17 SERIES TWIN COUPLING ASSEMBLY



PART NUMBER	DESCRIPTION
CP17-Y	Twin coupling assembly