


FEATURES	BENEFITS
<ul style="list-style-type: none"> • Single action • Positive locking mechanism 	<ul style="list-style-type: none"> • Strong & durable • Robust & hardwearing
SPECIFICATIONS	
Nominal flow diameter	5.5 mm (7/32")
Flow capacity	600 l/min (21.2 CFM)*
Max. working pressure	35 bar (508 psi)
Temperature range	-20°C to +100°C (-4°F to +212°F)
MATERIALS	
Coupling body	Nickel plated steel
Coupling back part	Nickel plated brass
Sleeve	Nickel plated steel
Valve	Brass
Springs, locking O-ring & balls	Stainless steel
Seals	NBR
Nipple	Nickel plated steel

Interchange
Vertex & Airflow Series 19



*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

COUPLINGS

NIPPLES

CP19 SERIES HOSE BARB



PART NUMBER	TUBE ID	METRIC EQ.
CP19-1002	1/4"	6 mm
CP19-1003	5/16"	8 mm
CP19-1004	3/8"	10 mm
CP19-1005	1/2"	13 mm

CP19 SERIES HOSE BARB



PART NUMBER	TUBE ID	METRIC EQ.
CP19-5002	1/4"	6 mm
CP19-5003	5/16"	8 mm
CP19-5004	3/8"	10 mm
CP19-5005	1/2"	13 mm

CP19 SERIES BSPT MALE



PART NUMBER	THREAD
CP19-1152	1/4" BSPT
CP19-1154	3/8" BSPT
CP19-1155	1/2" BSPT

CP19 SERIES BSPT MALE



PART NUMBER	THREAD
CP19-5152	1/4" BSPT
CP19-5154	3/8" BSPT
CP19-5155	1/2" BSPT

CP19 SERIES BSPP FEMALE



PART NUMBER	THREAD
CP19-1202	1/4" BSPP
CP19-1204	3/8" BSPP
CP19-1205	1/2" BSPP

CP19 SERIES BSPP FEMALE



PART NUMBER	THREAD
CP19-5202	1/4" BSPP
CP19-5204	3/8" BSPP
CP19-5205	1/2" BSPP

CP19 SERIES TWIN COUPLING ASSEMBLY



PART NUMBER	DESCRIPTION
CP19-Y	Twin coupling assembly