

LUBRICATION FITTINGS & ADAPTORS



PUSH-IN LUBRICATION FITTINGS

FEATURES / BENEFITS

- Suitable for oil & grease applications
- · For use with nylon tube

PUSH-IN STRAIGHT

SPECIFICATIONS

Max. working pressure Material

60 bar Nickel plated brass



PUSH-IN CONNECTOR NICKEL PLATED BRASS

PART NUMBER	TUBE OD	TUBE OD	
LU-1520	4 mm	4 mm	
LU-1530	6 mm	6 mm	

NICKEL PLATED BRASS			7900
PART NUMBER	THREAD	TUBE OD	
LU-1355	1/4" UNF	4 mm	
LU-1360	M6 x 1	4 mm	
LU-1370	M8 x 1	4 mm	
LU-1380	M10 x 1	4 mm	
LU-1390	1/8" BSPT	4 mm	
LU-1395	1/4" UNF	6 mm	
LU-1400	M6 x 1	6 mm	
LU-1410	M8 x 1	6 mm	
LU-1420	M10 x 1	6 mm	
LU-1430	1/8" BSPT	6 mm	

7900

PUSH-IN 90° ELBOW NICKEL PLATED BRASS

PART NUMBER	THREAD	TUBE OD	
LU-1435	1/4" UNF	4 mm	
LU-1440	M6 x 1	4 mm	
LU-1450	M8 x 1	4 mm	
LU-1460	M10 x 1	4 mm	
LU-1470	1/8" BSPT	6 mm	
LU-1480	M6 x 1	6 mm	
LU-1490	M8 x 1	6 mm	
LU-1500	M10 x 1	6 mm	
LU-1510	1/8" BSPT	6 mm	

PUSH-IN 90° SWIVEL ELBOW NICKEL PLATED BRASS



LUBRICATION ADAPTORS

- FEATURES / BENEFITS
- Suitable for oil & grease applications

		_	
1015		-	
CTATE .	1000		

45° ELBOW ADAPTOR ZINC NICKE

INC NICKEL COATED		75	
PART NUMBER	MALE THREAD	FEMALE THREAD	
LU-1580	M8 x 1	M8 x 1	
LU-1590	M10 x 1	M10 x 1	
LU-1600	1/8" BSPT	1/8" BSPT	

SPECIFICATIONS M

Max. working pressure	100 bar
Material	Zinc nickel coated

90° ELBOW ADAPTOR ZINC NICKEL COATED



PART NUMBER	MALE THREAD	FEMALE THREAD	
LU-1610	M6 x 1	M6 x 1	
LU-1620	M8 x 1	M8 x 1	
LU-1630	M10 x 1	M10 x 1	
LU-1640	1/8" BSPT	1/8" BSPT	