

ACETAL – RED / BLACK QUICK RELEASE FITTINGS

FEATURES

The special quick connector offers a fast & reliable push-to-connect mechanism. The outer sleeve locks the plug into the socket. When the plug is disconnected, the socket acts as a shut-off valve. A variety of plugs can be connected & used, suitable for hydraulic or pneumatic systems.

SPECIFICATIONS

Working pressure	Up to 14 bar (200 psi) at 20°C
Temperature range	4°C to 90°C (39°F to 194°F) subject to application
Colour	Red / black

MATERIALS

Body	Nylon 66
Internal parts	Acetal
Spring & ball	Stainless steel

CERTIFICATIONS & CONFORMITY



COUPLINGS

**QUICK RELEASE SOCKET
WITH NBR O-RING
BSPT FEMALE**


3860

PART NUMBER	THREAD
TF-22080004000	1/4" BSPT

NIPPLES

**PLUG
BSPT MALE**


3860

PART NUMBER	THREAD
TF-12081404006	1/4" BSPT

**PLUG
BSPT FEMALE**


3860

PART NUMBER	THREAD
TF-12081504006	1/4" BSPT

HOSETAIL PLUG


3860

PART NUMBER	HOSE ID
TF-12081645006	5 mm
TF-12081646006	6 mm
TF-12081648006	8 mm
TF-12081650006	10 mm
TF-12081652006	12 mm

Do you also need?

Reinforced PVC hose


RoHS 3
COMPLIANT
EU 2015/863



Find it on page 623, section ten