




FEATURES	BENEFITS
<ul style="list-style-type: none"> • Push to connect & lock • Twist sleeve 1/8 turn to unlock & release 	<ul style="list-style-type: none"> • Protects against accidental uncoupling
SPECIFICATIONS	
Flow capacity	850 l/min (30.0 CFM)*
Max. working pressure	17 bar (250 psi)
Min. burst pressure	140 bar (2030 psi)
Temperature range	-40°C to +107°C (-40°F to +225°F)
Locking device	Spring plates
Coupling material	Steel / aluminium
Nipple material	Hardened steel
Valve	Steel
Seal	NBR

Interchange
Series 17




*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

COUPLINGS

NIPPLES

399 SERIES HOSE BARB



5620

PART NUMBER	TUBE ID	METRIC EQ.
C103991002	1/4"	6 mm
C103991004	3/8"	10 mm


399 SERIES HOSE BARB



5620

PART NUMBER	TUBE ID	METRIC EQ.
C103995002	1/4"	6 mm
C103995003	5/16"	8 mm
C103995004	3/8"	10 mm
C103995005	1/2"	13 mm

399 SERIES BSPT MALE



5620

PART NUMBER	THREAD
C103991152	1/4" BSPT
C103991154	3/8" BSPT


399 SERIES BSPT MALE



5620

PART NUMBER	THREAD
C103995151	1/8" BSPT
C103995152	1/4" BSPT
C103995154	3/8" BSPT
C103995155	1/2" BSPT

399 SERIES BSPP FEMALE



5620

PART NUMBER	THREAD
C103991202	1/4" BSPP

399 SERIES BSPP FEMALE



5620

PART NUMBER	THREAD
C103995201	1/8" BSPP
C103995202	1/4" BSPP
C103995204	3/8" BSPP

Do you also need?



Rubber alloy hose



Find it on page 675, section ten