

## EAFM MIST SEPARATOR

### SPECIFICATIONS

Max. working pressure	10 bar
Working temperature	-5°C to +60°C (no freezing)
Filter precision	0.3 micron
Working medium	Clean air (after 40 µm filtration)
Bowl material	Polycarbonate
Max. inlet pressure	15 bar

New

### EAFM SERIES MIST SEPARATOR MANUAL DRAIN



3650

PART NUMBER	BODY SIZE	PORT SIZE	FLOW RATE
EM-EAFM2000-02	2000	1/4"	1300 l/min

### AUTO DRAIN

EM-EAFM3000-02C	3000	1/4"	2750 l/min
EM-EAFM3000-03C	3000	3/8"	2750 l/min
EM-EAFM4000-04C	4000	1/2"	4200 l/min

## EAF FILTER

### SPECIFICATIONS

Max. working pressure	10 bar
Working temperature	-5°C to +60°C (no freezing)
Filter precision	40 micron
Working medium	Clean air (after 40 µm filtration)
Bowl material	Polycarbonate
Max. inlet pressure	15 bar



3650

### EAF SERIES FILTER MANUAL DRAIN WITH BRACKET

PART NUMBER	BODY SIZE	PORT SIZE	FLOW RATE
EM-EAF2000-02	2000	1/4"	1300 l/min
EM-EAF3000-03	3000	3/8"	2750 l/min
EM-EAF4000-04	4000	1/2"	4200 l/min

### SPECIFICATIONS

Max. working pressure	10 bar
Working temperature	-5°C to +60°C (no freezing)
Filter precision	5 micron
Working medium	Clean air (after 40 µm filtration)
Bowl material	Polycarbonate
Max. inlet pressure	15 bar



3650

### EAF SERIES FILTER MANUAL DRAIN WITH BRACKET

PART NUMBER	BODY SIZE	PORT SIZE	FLOW RATE
EM-EAF2000-02-5M	2000	1/4"	1300 l/min
EM-EAF3000-03-5M	3000	3/8"	2750 l/min
EM-EAF3000-04-5M	4000	1/2"	4200 l/min

## EAR REGULATORS

### SPECIFICATIONS

Max. working pressure	10 bar
Working temperature	-5°C to +60°C (no freezing)
Working medium	Clean air (after 40 µm filtration)
Max. inlet pressure	15 bar
Adjustable pressure range	1.5 to 9 bar
Type	Relieving

### PANEL CUT OUT HOLE

BODY SIZE	Ø	MAX. PLATE THICKNESS
2000	31.5 mm	3.5 mm
3000	36.5 mm	3.0 mm
4000	52.5 mm	3.0 mm



3650

### EAR SERIES REGULATOR INTEGRAL GAUGE & BRACKET

PART NUMBER	BODY SIZE	PORT SIZE	FLOW RATE
EM-EAR2000-02	2000	1/4"	1300 l/min
EM-EAR3000-03	3000	3/8"	2750 l/min
EM-EAR4000-04	4000	1/2"	4200 l/min

## EAL LUBRICATOR

### SPECIFICATIONS

Max. working pressure	0.5 to 10 bar
Working temperature	-5°C to +60°C (no freezing)
Working medium	Clean air (after 40 µm filtration)
Bowl material	Polycarbonate
Max. inlet	15 bar



3650

### EAL SERIES LUBRICATOR WITH BRACKET

PART NUMBER	BODY SIZE	PORT SIZE	FLOW RATE
EM-EAL2000-02	2000	1/4"	2500 l/min
EM-EAL3000-03	3000	3/8"	4000 l/min
EM-EAL4000-04	4000	1/2"	5250 l/min