

FEATURES	BENEFITS
<ul style="list-style-type: none"> Two stage, self-venting release Compatible with genuine PCL standard adaptors Hard wearing steel construction with corrosion resistant finish Affordable safety solution 	<ul style="list-style-type: none"> Safe & simple to use Prevents hose whip Creates a safe compressed air environment Conforms to ISO4414:1998 & EN 983:1996
SPECIFICATIONS	
Nominal flow diameter	5 mm (3/16")
Flow capacity	1210 l/min (43.0 CFM)*
Max. working pressure	14 bar (200 psi)
Temperature range	-40°C to +100°C (-40°F to +212°F)
Coupling material	Steel

Interchange
PCL standard adaptor, Airflow, Vertex, Series 19 & 57

Single Shut-off

*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

COUPLINGS

SAFEFLOW SAFETY SERIES HOSE BARB



PART NUMBER	TUBE ID	METRIC EQ.
CSC21R	1/4"	6 mm
CSC21S	5/16"	8 mm
CSC21T	3/8"	10 mm

SAFEFLOW SAFETY SERIES BSPT MALE



PART NUMBER	THREAD
CSC21CM	1/4" BSPT
CSC21EM	3/8" BSPT
CSC21JM	1/2" BSPT

SAFEFLOW SAFETY SERIES BSPT FEMALE



PART NUMBER	THREAD
CSC21CF	1/4" BSPT
CSC21EF	3/8" BSPT
CSC21JF	1/2" BSPT

NIPPLES

295 SERIES HOSE BARB



PART NUMBER	TUBE ID	METRIC EQ.
C102955001	3/16"	5 mm
C102955002	1/4"	6 mm
C102955003	5/16"	8 mm
C102955004	3/8"	10 mm
C102955005	1/2"	13 mm

295 SERIES BSPT MALE



PART NUMBER	THREAD
C102955152	1/4" BSPT
C102955154	3/8" BSPT
C102955155	1/2" BSPT

295 SERIES BSPP FEMALE



PART NUMBER	THREAD
C102955202	1/4" BSPP
C102955204	3/8" BSPP
C102955205	1/2" BSPP



Did you know?

Products with safety benefits are indicated by a chevron at the bottom of their table