

FEATURES

- Series A airline couplings to BS AU 138a: 1980
- Series B airline couplings to BS AU 138b: 2000

SPECIFICATIONS


Max. working pressure	10 bar (145 psi)
Temperature range	-10°C to +80°C (+14°F to +176°F)
Series A body	Carbon steel 5 micron zinc plated & yellow passivate
Series B body	Carbon steel plated 12 micron zinc-iron with black passivate
Series B locking sleeve	Aluminium

Single Shut-off



COUPLINGS

TRACTOR AIRLINE SERIES A SELF SEALING VALVES



2540

PART NUMBER	THREAD	TYPE
ZVCM3501	1/2" BSPP	Service line
ZVCM3770	M22 x 1.5	Service line

TRACTOR AIRLINE SERIES A SELF SEALING VALVES



2540

PART NUMBER	THREAD	TYPE
ZVCF3400	1/2" BSPP	Emergency line / auxiliary
ZVCF3771	M22 x 1.5	Emergency line / auxiliary

TRACTOR AIRLINE SERIES A



2540

PART NUMBER	THREAD	TYPE
ZVCF3397	1/2" BSPP	Auxiliary
ZVCF3763	M22 x 1.5	Auxiliary

TRACTOR AIRLINE SERIES A



2540

PART NUMBER	THREAD	TYPE
ZVCF3397	1/2" BSPP	Emergency + service line
ZVCF3772	M22 x 1.5	Emergency + service line

TRACTOR AIRLINE SERIES B



2542

PART NUMBER	THREAD	TYPE
ZVCF4009	1/2" BSPP	Emergency line
ZVCF4004	M16 x 1.5	Emergency line
ZVCF4000	M22 x 1.5	Emergency line

TRACTOR AIRLINE SERIES B



2542

PART NUMBER	THREAD	TYPE
ZVCF4015	1/2" BSPP	Service line
ZVCF4003	M22 x 1.5	Service line

NIPPLES

TRAILER AIRLINE SERIES A



2540

PART NUMBER	THREAD	TYPE
ZVCM3075	1/2" BSPP	Auxiliary
ZVCM3734	M22 x 1.5	Auxiliary

TRAILER AIRLINE SERIES A VALVE LIFTER



2540

PART NUMBER	THREAD	TYPE
ZVCF3135	1/2" BSPP	Service line
ZVCF3774	M22 x 1.5	Service line

TRAILER AIRLINE SERIES A



2540

PART NUMBER	THREAD	TYPE
ZVCM3074	1/2" BSPP	Emergency + service line
ZVCM3733	M22 x 1.5	Emergency + service line

TRAILER AIRLINE SERIES B



2542

PART NUMBER	THREAD	TYPE
ZVCM4014	1/2" BSPP	Emergency line
ZVCM4001	M22 x 1.5	Emergency line

TRAILER AIRLINE SERIES B



2542

PART NUMBER	THREAD	TYPE
ZVCM4010	1/2" BSPP	Service line
ZVCM4071	M16 x 1.5	Service line
ZVCM4002	M22 x 1.5	Service line