


FEATURES	BENEFITS
<ul style="list-style-type: none"> <li>• One hand operation to connect</li> <li>• Two hand operation to disconnect</li> <li>• Extremely high airflow rate</li> <li>• Grip friendly locking sleeve</li> </ul>	<ul style="list-style-type: none"> <li>• Prevents unintentional disconnection</li> <li>• Perfect for use in damp / wet &amp; corrosive environments</li> </ul>
SPECIFICATIONS	
Nominal flow diameter	7.4 mm (9/32")
Flow capacity	1950 l/min (68.8 CFM)*
Max. working pressure	35 bar (507 psi)
Min. burst pressure	140 bar (2030 psi)
Temperature range	-30°C to +100°C (-22°F to +212°F)
Coupling material	Nickel plated brass
Nipple material	Nickel plated brass

NPT threads are available



Not actual size

### Single Shut-off



\*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi).

## COUPLINGS

### 341 SERIES HOSE BARB



500

PART NUMBER	TUBE ID	METRIC EQ.
C103411034	5/16"	8 mm
C103411004	3/8"	10 mm

## NIPPLES

### 341 SERIES HOSE BARB



500

PART NUMBER	TUBE ID	METRIC EQ.
C103415002	1/4"	6 mm
C103415003	5/16"	8 mm
C103415004	3/8"	10 mm


### 341 SERIES BSPT MALE WITH LOCTITE DRY-SEAL®



500

PART NUMBER	THREAD
C103411152	1/4" BSPT
C103411154	3/8" BSPT
C103411155	1/2" BSPT

### 341 SERIES BSPT MALE



500

PART NUMBER	THREAD
C103415152	1/4" BSPT
C103415154	3/8" BSPT
C103415155	1/2" BSPT

### 341 SERIES BSPP FEMALE



500

PART NUMBER	THREAD
C103411202	1/4" BSPP
C103411204	3/8" BSPP
C103411205	1/2" BSPP

### 341 SERIES BSPP FEMALE



500

PART NUMBER	THREAD
C103415202	1/4" BSPP
C103415204	3/8" BSPP
C103415205	1/2" BSPP

Do you also need?



## Breathing air hose

Spiral anti-spark polyurethane tube



Find it on page 654, section ten