

STANDARD MINI BALL VALVES

APPLICATIONS

- Pneumatic, domestic & hydraulic installations
- Hot water
- Gasoline, fuel
- Oils, gas-oil
- Kerosene
- Acids
- Compressed air



2250

MINI

BSPP FEMALE

PART NUMBER	THREAD	PRESSURE
B/V10-04	1/4" BSPP	15 bar
B/V10-06	3/8" BSPP	15 bar
B/V10-08	1/2" BSPP	15 bar

SPECIFICATIONS

Temperature range	-10°C to +90°C (14°F to 194°F)
-------------------	--------------------------------

MATERIALS

Ball valve	Brass
Handle	Plastic
Seal	PTFE



2250

MINI

BSPP MALE / BSPP FEMALE

PART NUMBER	THREAD	PRESSURE
B/V11-04	1/4" BSPP	15 bar
B/V11-06	3/8" BSPP	15 bar
B/V11-08	1/2" BSPP	15 bar

REDUCED BORE MINI BALL VALVES – STAINLESS STEEL

APPLICATIONS

- Pneumatic, domestic & hydraulic installations
- Hot water
- Gasoline, fuel
- Oils, gas-oil
- Kerosene
- Acids
- Compressed air



2220

REDUCED BORE MINI BALL VALVE BSPP MALE / BSPP FEMALE

PART NUMBER	THREAD	WORKING PRESSURE
SJ-B/V11-04	1/4" BSPP	1000 psi
SJ-B/V11-06	3/8" BSPP	1000 psi
SJ-B/V11-08	1/2" BSPP	1000 psi

SPECIFICATIONS

Temperature range	-50°C to +232°C (-58°F to +450°F)
-------------------	-----------------------------------

Thread details	ISO 228/1 BSPP
----------------	----------------

MATERIALS

Body & ball	CF8M/CF8
Seat	15% R-PTFE
Stem	304 stainless steel



2220

REDUCED BORE MINI BALL VALVE BSPP FEMALE

PART NUMBER	THREAD	WORKING PRESSURE
SJ-B/V10-04	1/4" BSPP	1000 psi
SJ-B/V10-06	3/8" BSPP	1000 psi
SJ-B/V10-08	1/2" BSPP	1000 psi

HIGH PRESSURE MINI BALL VALVES

FEATURES

- RoSH compliant
- Dual sealing system allows valve to be operated in either direction making installation easier
- No metal-to-metal moving parts
- No maintenance required
- Silicone-free lubricant on all seals
- Handle / stem clearly shows ball position



2255

HIGH PRESSURE WITH SCREWDRIVER SLOT BSPP FEMALE

PART NUMBER	THREAD	PRESSURE
B/V-S35BF3	1/4" BSPP	30 bar
B/V-S35CF3	3/8" BSPP	30 bar
B/V-S35DF3	1/2" BSPP	30 bar

SPECIFICATIONS

Temperature range	-20°C to +120°C (-4°F to +250°F)
-------------------	----------------------------------

MATERIALS

Ball valve	Brass
Handle	Reinforced nylon
Seal	PTFE



2255

HIGH PRESSURE WITH SCREWDRIVER SLOT BSPP MALE / BSPP FEMALE

PART NUMBER	THREAD	PRESSURE
B/V-S35AM3	1/8" BSPP	30 bar
B/V-S35BM3	1/4" BSPP	30 bar
B/V-S35CM3	3/8" BSPP	30 bar
B/V-S35DM3	1/2" BSPP	30 bar