

STANDARD MINI BALL VALVES

APPLICATIONS

- Pneumatic, domestic & hydraulic installations
- Hot water
- Gasoline, fuel
- Oils, gas-oil
- Kerosene
- Acids
- Compressed air



2250

MINI

BSPP FEMALE

| PART NUMBER | THREAD | PRESSURE |
|-------------|-----------|----------|
| B/V10-04 | 1/4" BSPP | 15 bar |
| B/V10-06 | 3/8" BSPP | 15 bar |
| B/V10-08 | 1/2" BSPP | 15 bar |

SPECIFICATIONS

| | |
|-------------------|--------------------------------|
| Temperature range | -10°C to +90°C (14°F to 194°F) |
| MATERIALS | |
| Ball valve | Brass |
| Handle | Plastic |
| Seal | PTFE |



2250

MINI

BSPP MALE / BSPP FEMALE

| PART NUMBER | THREAD | PRESSURE |
|-------------|-----------|----------|
| B/V11-04 | 1/4" BSPP | 15 bar |
| B/V11-06 | 3/8" BSPP | 15 bar |
| B/V11-08 | 1/2" BSPP | 15 bar |

REDUCED BORE MINI BALL VALVES – STAINLESS STEEL

APPLICATIONS

- Pneumatic, domestic & hydraulic installations
- Hot water
- Gasoline, fuel
- Oils, gas-oil
- Kerosene
- Acids
- Compressed air



2220

REDUCED BORE MINI BALL VALVE BSPP MALE / BSPP FEMALE

| PART NUMBER | THREAD | WORKING PRESSURE |
|-------------|-----------|------------------|
| SJ-B/V11-04 | 1/4" BSPP | 1000 psi |
| SJ-B/V11-06 | 3/8" BSPP | 1000 psi |
| SJ-B/V11-08 | 1/2" BSPP | 1000 psi |

SPECIFICATIONS

| | |
|-------------------|-----------------------------------|
| Temperature range | -50°C to +232°C (-58°F to +450°F) |
| Thread details | ISO 228/1 BSPP |
| MATERIALS | |
| Body & ball | CF8M/CF8 |
| Seat | 15% R-PTFE |
| Stem | 304 stainless steel |



2220

REDUCED BORE MINI BALL VALVE BSPP FEMALE

| PART NUMBER | THREAD | WORKING PRESSURE |
|-------------|-----------|------------------|
| SJ-B/V10-04 | 1/4" BSPP | 1000 psi |
| SJ-B/V10-06 | 3/8" BSPP | 1000 psi |
| SJ-B/V10-08 | 1/2" BSPP | 1000 psi |

HIGH PRESSURE MINI BALL VALVES

FEATURES

- RoSH compliant
- Dual sealing system allows valve to be operated in either direction making installation easier
- No metal-to-metal moving parts
- No maintenance required
- Silicone-free lubricant on all seals
- Handle / stem clearly shows ball position



2255

HIGH PRESSURE WITH SCREWDRIVER SLOT BSPP FEMALE

| PART NUMBER | THREAD | PRESSURE |
|-------------|-----------|----------|
| B/V-S35BF3 | 1/4" BSPP | 30 bar |
| B/V-S35CF3 | 3/8" BSPP | 30 bar |
| B/V-S35DF3 | 1/2" BSPP | 30 bar |

SPECIFICATIONS

| | |
|-------------------|----------------------------------|
| Temperature range | -20°C to +120°C (-4°F to +250°F) |
| MATERIALS | |
| Ball valve | Brass |
| Handle | Reinforced nylon |
| Seal | PTFE |



2255

HIGH PRESSURE WITH SCREWDRIVER SLOT BSPP MALE / BSPP FEMALE

| PART NUMBER | THREAD | PRESSURE |
|-------------|-----------|----------|
| B/V-S35AM3 | 1/8" BSPP | 30 bar |
| B/V-S35BM3 | 1/4" BSPP | 30 bar |
| B/V-S35CM3 | 3/8" BSPP | 30 bar |
| B/V-S35DM3 | 1/2" BSPP | 30 bar |