

FULL FLOW BALL VALVES

APPLICATIONS

- Pneumatic, domestic & hydraulic installations
- Hot water
- Gasoline, fuel
- Oils, gas-oil
- Kerosene
- Acids
- Compressed air

SPECIFICATIONS

Temperature range	-10°C to +90°C (14°F to 194°F)
-------------------	--------------------------------

MATERIALS

Ball valve	Brass
Handle	Steel
Seal	PTFE



**FULL FLOW
BSPP FEMALE**

2250



**FULL FLOW
BSPP MALE / BSPP FEMALE**

2250

PART NUMBER	THREAD	PRESSURE
B/V12-04	1/4" BSPP	25 bar
B/V12-06	3/8" BSPP	25 bar
B/V12-08	1/2" BSPP	25 bar
B/V12-12	3/4" BSPP	25 bar
B/V12-16	1" BSPP	25 bar
B/V12-20	1 1/4" BSPP	25 bar
B/V12-24	1 1/2" BSPP	25 bar
B/V12-32	2" BSPP	25 bar

PART NUMBER	THREAD	PRESSURE
B/V14-04	1/4" BSPP	25 bar
B/V14-06	3/8" BSPP	25 bar
B/V14-08	1/2" BSPP	25 bar
B/V14-12	3/4" BSPP	25 bar
B/V14-16	1" BSPP	25 bar
B/V14-20	1 1/4" BSPP	25 bar
B/V14-24	1 1/2" BSPP	25 bar
B/V14-32	2" BSPP	25 bar

FULL FLOW GAS APPROVED BALL VALVE

APPLICATIONS

- Pneumatic, domestic & hydraulic installations
- Hot water
- Compressed air



SPECIFICATIONS

Max. pressure	1/4" – 2": 40 bar
Working temperature	-20°C to +140°C (-4°F to +284°F)

SPECIFICATIONS – GAS DISTRIBUTION

Max. pressure	1/4" – 4": 5 bar
Working temperature	-20°C to +60°C (-4°F to 140°F)

MATERIALS

Ball valve	Brass
Handle	Steel
Seal	PTFE



**FULL FLOW
BSPP FEMALE – GAS APPROVED**

2250



**FULL FLOW
BSPP MALE / BSPP FEMALE – GAS APPROVED**

2250

PART NUMBER	THREAD	PRESSURE
B/V13-04	1/4" BSPP	40 bar
B/V13-06	3/8" BSPP	40 bar
B/V13-08	1/2" BSPP	40 bar
B/V13-12	3/4" BSPP	40 bar
B/V13-16	1" BSPP	40 bar
B/V13-20	1 1/4" BSPP	40 bar
B/V13-24	1 1/2" BSPP	40 bar
B/V13-32	2" BSPP	40 bar

PART NUMBER	THREAD	PRESSURE
B/V15-04	1/4" BSPP	40 bar
B/V15-06	3/8" BSPP	40 bar
B/V15-08	1/2" BSPP	40 bar
B/V15-12	3/4" BSPP	40 bar
B/V15-16	1" BSPP	40 bar
B/V15-20	1 1/4" BSPP	40 bar
B/V15-24	1 1/2" BSPP	40 bar
B/V15-32	2" BSPP	40 bar