

ONE & TWO PIECE SCREWED

SPECIFICATIONS

Temperature range -50°C to +232°C (60°F to 450°F)

MATERIALS

Body	ASTM A-351 Gr.CF8M (DIN 1.4408)
Ball	316 stainless steel
Seat	PTFE
Stem	316 stainless steel

THREAD DETAILS

ANSI B1.20.1 (NPT)
DIN 259/DIN 2999
ISO 228: BSP: PT



2220

**ONE PIECE BALL VALVE
BSPP FEMALE
REDUCED BORE**

PART NUMBER	THREAD	WORKING PRESSURE
SJ-V10-04	1/4" BSPP	55 bar
SJ-V10-06	3/8" BSPP	55 bar
SJ-V10-08	1/2" BSPP	55 bar
SJ-V10-12	3/4" BSPP	55 bar
SJ-V10-16	1" BSPP	55 bar
SJ-V10-20	1 1/4" BSPP	55 bar
SJ-V10-24	1 1/2" BSPP	55 bar
SJ-V10-32	2" BSPP	55 bar

THREE PIECE SCREWED & CHECK VALVE

SPECIFICATIONS

Temperature range -51°C to +232°C (-60°F to +450°F)

MATERIALS

Body	ASTM A-351 Gr.CF8M (DIN 1.4408)
Ball	316 stainless steel
Seat	PTFE
Stem	316 stainless steel



2220

**THREE PIECE BALL VALVE
BSPP FEMALE
FULL FLOW**

PART NUMBER	THREAD	WORKING PRESSURE
SJ-V30-04	1/4" BSPP	69 bar
SJ-V30-06	3/8" BSPP	69 bar
SJ-V30-08	1/2" BSPP	69 bar
SJ-V30-12	3/4" BSPP	69 bar
SJ-V30-16	1" BSPP	69 bar
SJ-V30-20	1 1/4" BSPP	69 bar
SJ-V30-24	1 1/2" BSPP	69 bar
SJ-V30-32	2" BSPP	69 bar



2220

**TWO PIECE BALL VALVE
BSPP FEMALE – FULL FLOW**

PART NUMBER	THREAD	WORKING PRESSURE
SJ-V20-04	1/4" BSPP	69 bar
SJ-V20-06	3/8" BSPP	69 bar
SJ-V20-08	1/2" BSPP	69 bar
SJ-V20-12	3/4" BSPP	69 bar
SJ-V20-16	1" BSPP	69 bar
SJ-V20-20	1 1/4" BSPP	69 bar
SJ-V20-24	1 1/2" BSPP	69 bar
SJ-V20-32	2" BSPP	69 bar

Do you also need?

**PTFE lined
convoluted hose**

Find it on page 192, section four