

## STANDARD FLOW BALL VALVES – VIENNA®

### FEATURES

Suitable for domestic water services, heating & air-conditioning plants, & compressed air systems.



**VIENNA® STANDARD FLOW  
BSPP FEMALE – ISO228**


2200

### SPECIFICATIONS

Temperature range -20°C to +150°C (-4°F to +302°F) in absence of steam

### MATERIALS

Body Nickel plated brass  
Flat lever handle Lined steel



**VIENNA® STANDARD FLOW  
BSPP MALE /  
BSPP FEMALE – ISO228**

2200

PART NUMBER	THREAD	PRESSURE
● B/V2216-04	1/4" BSPP	50 bar
● B/V2216-06	3/8" BSPP	50 bar
● B/V2216-08	1/2" BSPP	30 bar
● B/V2216-12	3/4" BSPP	30 bar
● B/V2216-16	1" BSPP	30 bar
● B/V2216-20	1 1/4" BSPP	25 bar
● B/V2216-24	1 1/2" BSPP	25 bar
● B/V2216-32	2" BSPP	25 bar

PART NUMBER	THREAD	PRESSURE
● B/V2217-04	1/4" BSPP	50 bar
● B/V2217-06	3/8" BSPP	50 bar
● B/V2217-08	1/2" BSPP	30 bar
● B/V2217-12	3/4" BSPP	30 bar
● B/V2217-16	1" BSPP	30 bar
● B/V2217-20	1 1/4" BSPP	25 bar
● B/V2217-24	1 1/2" BSPP	25 bar
● B/V2217-32	2" BSPP	25 bar

## REDUCED FLOW BALL VALVES – ORIENT®

### DESCRIPTION

Suitable for domestic water services, heating & air conditioning plants, & compressed air systems.



**ORIENT® REDUCED FLOW  
BSPP FEMALE – ISO228**

2200

### SPECIFICATIONS

Temperature range -20°C to +150°C (-4°F to +302°F) in absence of steam

### MATERIALS

Body Nickel plated brass  
Lever handle Steel  
T handle Aluminium



**ORIENT® REDUCED FLOW  
BSPP MALE /  
BSPP FEMALE – ISO228**

2200

PART NUMBER	THREAD	PRESSURE
● B/V2111-08	1/2" BSPP	50 bar
● B/V2111-12	3/4" BSPP	40 bar
● B/V2111-16	1" BSPP	40 bar
● B/V2111-20	1 1/4" BSPP	30 bar
● B/V2111-24	1 1/2" BSPP	30 bar

PART NUMBER	THREAD	PRESSURE
● B/V2112-08	1/2" BSPP	50 bar
● B/V2112-12	3/4" BSPP	40 bar
● B/V2112-16	1" BSPP	40 bar

**ORIENT® REDUCED FLOW  
T HANDLE  
BSPP FEMALE – ISO228**



2200

**ORIENT® REDUCED FLOW  
T HANDLE  
BSPP MALE /  
BSPP FEMALE – ISO228**



2200

PART NUMBER	THREAD	PRESSURE
● B/V2113-08	1/2" BSPP	50 bar
● B/V2113-12	3/4" BSPP	40 bar
● B/V2113-16	1" BSPP	40 bar

PART NUMBER	THREAD	PRESSURE
● B/V2114-08	1/2" BSPP	50 bar
● B/V2114-12	3/4" BSPP	40 bar
● B/V2114-16	1" BSPP	40 bar