

SWING, CHECK & FOOT VALVES & STRAINERS



CHECK VALVES

DESCRIPTION

Suitable for domestic water services, heating & air conditioning plants, & compressed air systems. Can be installed in any position: vertical, horizontal, oblique. Suitable for use with gasoline & fuels in general

SPECIFICATIONS

Temperature range	-20°C to +100°C (-4°F to +212°F) with water -20°C to +150°C (-4°F to +302°F) with fluid hydrocarbons or compressed air
MATERIALS	
Body	Brass
Plate	Stainless steel
Seal	FKM
Spring	Stainless steel

ROMA® CHECK VALVE BSPP FEMALE –	ISO 228/1	Noma-	2200
PART NUMBER	THREAD	PRESSURE	
B/V3104-06	3/8" BSPP	25 bar	
B/V3104-08	1/2" BSPP	25 bar	
B/V3104-12	3/4" BSPP	25 bar	
B/V3104-16	1" BSPP	25 bar	
B/V3104-20	1 1/4" BSPP	18 bar	
B/V3104-24	1 1/2" BSPP	18 bar	
B/V3104-32	2" BSPP	18 bar	

STRAINERS FOR USE WITH EUROPA®, YORK®, BLOCK®, ROMA®, CHECK VALVES



STAINLESS STEEL NYLON THREAD **BSPP MALE**

THREAD	MICRON	
3/8" BSPP	1200 µm	
1/2" BSPP	1200 µm	
3/4" BSPP	1200 µm	
1" BSPP	1200 µm	
1 1/4" BSPP	1200 µm	
1 1/2" BSPP	1200 µm	
2" BSPP	1200 µm	
2 1/2" BSPP	1700 µm	
3" BSPP	1700 µm	
4" BSPP	1700 µm	
	3/8" BSPP 1/2" BSPP 3/4" BSPP 1" BSPP 1 1/4" BSPP 1 1/2" BSPP 2" BSPP 2 1/2" BSPP 3" BSPP	3/8" BSPP 1200 µm 1/2" BSPP 1200 µm 3/4" BSPP 1200 µm 1" BSPP 1200 µm 1 1/4" BSPP 1200 µm 1 1/2" BSPP 1200 µm 2" BSPP 1200 µm 2 1/2" BSPP 1200 µm 3" BSPP 1700 µm

1		
1		
- 3		
- 3		
- 1	-	
- 1	-	
- 1	-	3

POLYMER **BSPP MALE**

2200

PART NUMBER	THREAD
B/V3107-06	3/8" BSPP
B/V3107-08	1/2" BSPP
B/V3107-12	3/4" BSPP
B/V3107-16	1" BSPP
B/V3107-20	1 1/4" BSPP
B/V3107-24	1 1/2" BSPP
B/V3107-32	2" BSPP

SWING CHECK & FOOT VALVES

DESCRIPTION

Suitable for domestic water services, heating & air conditioning plants, compressed air systems. They can be installed vertically.



FOOT VALVE **BSPP FEMALE**

PART NUMBER	THREAD		
		PRESSURE	
B/V3140-08	1/2" BSPP	10 bar	
B/V3140-12	3/4" BSPP	10 bar	
B/V3140-16	1" BSPP	10 bar	
B/V3140-20	1 1/4" BSPP	8 bar	
B/V3140-24	1 1/2" BSPP	8 bar	
B/V3140-32	2" BSPP	8 bar	
B/V3140-40	2 1/2" BSPP	6 bar	
B/V3140-48	3" BSPP	6 bar	
B/V3140-64	4" BSPP	6 bar	

Temperature range	0°C to 90°C (32°F to 194°F) with water
MATERIALS	
Body & plate	Brass
Seals	NBR
Foot valve strainer washer	Fibre
Cracking pressure	0.1 psi

SWING CHECK VALVE METAL SEAT **BSPP FEMALE**

SPECIFICATIONS



PART NUMBER THREAD PRESSURE B/V3130-06 3/8" BSPP 16 bar B/V3130-08 1/2" BSPP 16 bar B/V3130-12 3/4" BSPP 16 bar B/V3130-12 3/4" BSPP 16 bar B/V3130-12 3/4" BSPP 12 bar B/V3130-16 1" BSPP 12 bar B/V3130-20 1 1/4" BSPP 10 bar B/V3130-24 1 1/2" BSPP 10 bar B/V3130-32 2" BSPP 10 bar B/V3130-40 2 1/2" BSPP 8 bar B/V3130-44 3" BSPP 8 bar B/V3130-64 4" BSPP 8 bar	-			
B/V3130-08 1/2" BSPP 16 bar B/V3130-12 3/4" BSPP 16 bar B/V3130-16 1" BSPP 12 bar B/V3130-20 1 1/4" BSPP 10 bar B/V3130-24 1 1/2" BSPP 10 bar B/V3130-32 2" BSPP 10 bar B/V3130-34 2 1/2" BSPP 8 bar B/V3130-48 3" BSPP 8 bar	PART NUMBER	THREAD	PRESSURE	
B/V3130-12 3/4" BSPP 16 bar B/V3130-16 1" BSPP 12 bar B/V3130-20 1 1/4" BSPP 10 bar B/V3130-24 1 1/2" BSPP 10 bar B/V3130-32 2" BSPP 10 bar B/V3130-40 2 1/2" BSPP 8 bar B/V3130-48 3" BSPP 8 bar	B/V3130-06	3/8" BSPP	16 bar	
B/V3130-16 1" BSPP 12 bar B/V3130-20 1 1/4" BSPP 10 bar B/V3130-24 1 1/2" BSPP 10 bar B/V3130-32 2" BSPP 10 bar B/V3130-40 2 1/2" BSPP 8 bar B/V3130-48 3" BSPP 8 bar	B/V3130-08	1/2" BSPP	16 bar	
B/V3130-20 1 1/4" BSPP 10 bar B/V3130-24 1 1/2" BSPP 10 bar B/V3130-32 2" BSPP 10 bar B/V3130-40 2 1/2" BSPP 8 bar B/V3130-48 3" BSPP 8 bar	B/V3130-12	3/4" BSPP	16 bar	
B/V3130-24 1 1/2" BSPP 10 bar B/V3130-32 2" BSPP 10 bar B/V3130-40 2 1/2" BSPP 8 bar B/V3130-48 3" BSPP 8 bar	B/V3130-16	1" BSPP	12 bar	
B/V3130-32 2" BSPP 10 bar B/V3130-40 2 1/2" BSPP 8 bar B/V3130-48 3" BSPP 8 bar	B/V3130-20	1 1/4" BSPP	10 bar	
B/V3130-40 2 1/2" BSPP 8 bar B/V3130-48 3" BSPP 8 bar	B/V3130-24	1 1/2" BSPP	10 bar	
B/V3130-48 3" BSPP 8 bar	B/V3130-32	2" BSPP	10 bar	
	B/V3130-40	2 1/2" BSPP	8 bar	
B/V3130-64 4" BSPP 8 bar	B/V3130-48	3" BSPP	8 bar	
	B/V3130-64	4" BSPP	8 bar	

2200

2200