

Y STRAINERS

DESCRIPTION

Suitable for domestic water services, heating & air conditioning plants & compressed air systems.

SPECIFICATIONS

Temperature range -20°C to +110°C (-4°F to +230°F)
in absence of steam

MATERIALS	192 SERIES	193 SERIES
Body	Brass	Nickel plated brass

200 µm filtration available in sizes 1/4" to 2"
Please ask your distributor for further details



2200

192 SERIES – BSPP FEMALE 500 MICRON FILTRATION

PART NUMBER	THREAD	PRESSURE
B/V2192-04	1/4" BSPP	20 bar
B/V2192-06	3/8" BSPP	20 bar
B/V2192-08	1/2" BSPP	20 bar
B/V2192-12	3/4" BSPP	20 bar
B/V2192-16	1" BSPP	20 bar
B/V2192-20	1 1/4" BSPP	20 bar
B/V2192-24	1 1/2" BSPP	20 bar
B/V2192-32	2" BSPP	20 bar

800 MICRON FILTRATION

B/V2192-40	2 1/2" BSPP	16 bar
B/V2192-48	3" BSPP	16 bar
B/V2192-64	4" BSPP	16 bar



2200

193 SERIES – BSPP FEMALE 500 MICRON FILTRATION

PART NUMBER	THREAD	PRESSURE
B/V219350-04	1/4" BSPP	20 bar
B/V219350-06	3/8" BSPP	20 bar
B/V219350-08	1/2" BSPP	20 bar
B/V219350-12	3/4" BSPP	20 bar
B/V219350-16	1" BSPP	20 bar
B/V219350-20	1 1/4" BSPP	20 bar
B/V219350-24	1 1/2" BSPP	20 bar
B/V219350-32	2" BSPP	20 bar

300 MICRON FILTRATION

B/V219330-04	1/4" BSPP	20 bar
B/V219330-06	3/8" BSPP	20 bar
B/V219330-08	1/2" BSPP	20 bar
B/V219330-12	3/4" BSPP	20 bar
B/V219330-16	1" BSPP	20 bar
B/V219330-20	1 1/4" BSPP	20 bar
B/V219330-24	1 1/2" BSPP	20 bar
B/V219330-32	2" BSPP	20 bar

50 MICRON FILTRATION

B/V219305-04	1/4" BSPP	20 bar
B/V219305-06	3/8" BSPP	20 bar
B/V219305-08	1/2" BSPP	20 bar
B/V219305-12	3/4" BSPP	20 bar
B/V219305-16	1" BSPP	20 bar
B/V219305-20	1 1/4" BSPP	20 bar
B/V219305-24	1 1/2" BSPP	20 bar
B/V219305-32	2" BSPP	20 bar

PRESSURE REDUCING VALVES

DESCRIPTION

Suitable for domestic water services, heating & air conditioning plants & compressed air systems.

SPECIFICATIONS

Temperature range	0°C to 80°C
Max. inlet pressure	25 bar
Outlet pressure	1/2", 3/4", 1" = 1 to 5.5 bar 1 1/4" – 2" = 1 to 6 bar



* 1/2", 3/4" & 1" sizes are WRAS approved to 16 bar



2200

PRESSURE REDUCING VALVES ANTIDEZINCIFICATION BRASS BSPP FEMALE – ISO228

PART NUMBER	THREAD	PRESSURE
B/V4243-08*	1/2" BSPP	25 bar
B/V4243-12*	3/4" BSPP	25 bar
B/V4243-16*	1" BSPP	25 bar
B/V4243-20	1 1/4" BSPP	25 bar
B/V4243-24	1 1/2" BSPP	25 bar
B/V4243-32	2" BSPP	25 bar

New

PRESSURE REDUCING VALVES NICKEL PLATED BRASS BSPP FEMALE – ISO228

PART NUMBER	THREAD	PRESSURE
B/V1430-08	1/2" BSPP	25 bar
B/V1430-12	3/4" BSPP	25 bar
B/V1430-16	1" BSPP	25 bar
B/V1430-20	1 1/4" BSPP	25 bar
B/V1430-24	1 1/2" BSPP	25 bar
B/V1430-32	2" BSPP	25 bar
B/V1430-40	2 1/2" BSPP	25 bar
B/V1430-48	3" BSPP	25 bar
B/V1430-64	4" BSPP	25 bar



2200

CARTRIDGES

192 / 193 SERIES 500 MICRON FILTRATION

PART NUMBER	FOR STRAINERS
B/V2192CA-04	1/4", 3/8", 1/2"
B/V2192CA-12	3/4"
B/V2192CA-16	1"
B/V2192CA-20	1 1/4"
B/V2192CA-24	1 1/2"
B/V2192CA-32	2"

800 MICRON FILTRATION

B/V2192CA-40	2 1/2"
B/V2192CA-48	3"
B/V2192CA-64	4"



2200