

### APPLICATIONS

- Industrial, pneumatic, domestic & hydraulic installations
- Compressed air
- Water
- Oils
- Gas

### SPECIFICATIONS

Temperature range -18°C to +80°C (0°F to 176°F)

### MATERIALS

Body Chrome nickel plated brass unless otherwise stated



### FULL FLOW BSPT FEMALE – ISO7/1

1450

### FULL FLOW BSPT MALE / BSPT FEMALE ISO7/1

1450

PART NUMBER	THREAD	PRESSURE
B/V6300-02	1/8" BSPT	20 bar
B/V6300-04	1/4" BSPT	20 bar
B/V6300-06	3/8" BSPT	20 bar
B/V6300-08	1/2" BSPT	20 bar
B/V6300-12	3/4" BSPT	20 bar

PART NUMBER	THREAD	THREAD	PRESSURE
B/V6310-02	1/8" BSPT	1/8" BSPT	20 bar
B/V6310-03	1/4" BSPT	1/8" BSPT	20 bar
B/V6310-04	1/4" BSPT	1/4" BSPT	20 bar
B/V6310-06	3/8" BSPT	3/8" BSPT	20 bar
B/V6310-08	1/2" BSPT	1/2" BSPT	20 bar
B/V6310-12	3/4" BSPT	3/4" BSPT	20 bar

New



### FULL FLOW FOOT MOUNTED BSPP FEMALE – ISO7/1

1450

### FULL FLOW BSPT MALE THREAD – ISO7/1 BSPT MALE THREAD – ISO228

1450

PART NUMBER	THREAD	PRESSURE
B/V6490-04	1/4" BSPP	20 bar
B/V6490-06	3/8" BSPP	20 bar

PART NUMBER	THREAD	THREAD	PRESSURE
B/V6330-022	1/8" BSPT	1/8" BSPP	20 bar
B/V6330-024	1/8" BSPT	1/4" BSPP	20 bar
B/V6330-042	1/4" BSPT	1/8" BSPP	20 bar
B/V6330-044	1/4" BSPT	1/4" BSPP	20 bar
B/V6330-066	3/8" BSPT	3/8" BSPP	20 bar
B/V6330-088	1/2" BSPT	1/2" BSPP	20 bar
B/V6330-12	3/4" BSPT	3/4" BSPP	20 bar



### FULL FLOW BSPP MALE – ISO228 BSPT FEMALE – ISO7/1

1450

### FULL FLOW BSPP MALE – ISO228 BSPP FEMALE – ISO228

1450

PART NUMBER	MALE THREAD	FEMALE THREAD	PRESSURE
B/V6320-022	1/8" BSPP	1/8" BSPT	20 bar
B/V6320-042	1/4" BSPP	1/8" BSPT	20 bar
B/V6320-044	1/4" BSPP	1/4" BSPT	20 bar
B/V6320-066	3/8" BSPP	3/8" BSPT	20 bar
B/V6320-088	1/2" BSPP	1/2" BSPT	20 bar
B/V6320-12	3/4" BSPP	3/4" BSPT	20 bar

PART NUMBER	THREAD	THREAD	PRESSURE
B/V6410-022	1/8" BSPP	1/8" BSPP	20 bar
B/V6410-042	1/4" BSPP	1/8" BSPP	20 bar
B/V6410-044	1/4" BSPP	1/4" BSPP	20 bar
B/V6410-066	3/8" BSPP	3/8" BSPP	20 bar
B/V6410-088	1/2" BSPP	1/2" BSPP	20 bar
B/V6410-12	3/4" BSPP	3/4" BSPP	20 bar



### FULL FLOW BSPP FEMALE – ISO228

1450

### FULL FLOW BSPP MALE – ISO228

1450

PART NUMBER	THREAD	PRESSURE
B/V6400-02	1/8" BSPP	20 bar
B/V6400-04	1/4" BSPP	20 bar
B/V6400-06	3/8" BSPP	20 bar
B/V6400-08	1/2" BSPP	20 bar
B/V6400-12	3/4" BSPP	20 bar

PART NUMBER	THREAD	THREAD	PRESSURE
B/V6420-02	1/8" BSPP	1/8" BSPP	20 bar
B/V6420-03	1/8" BSPP	1/4" BSPP	20 bar
B/V6420-04	1/4" BSPP	1/4" BSPP	20 bar
B/V6420-05	3/8" BSPP	1/4" BSPP	20 bar
B/V6420-06	3/8" BSPP	3/8" BSPP	20 bar
B/V6420-07	1/2" BSPP	3/8" BSPP	20 bar
B/V6420-08	1/2" BSPP	1/2" BSPP	20 bar
B/V6420-09	1/2" BSPP	3/4" BSPP	20 bar
B/V6420-12	3/4" BSPP	3/4" BSPP	20 bar