

## COPLEXEL REINFORCED PVC HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> <li>Compressed air</li> <li>Water</li> <li>Chemicals</li> <li>Gas</li> </ul>	<ul style="list-style-type: none"> <li>Resistant to a wide range of chemicals</li> <li>Silicone free</li> <li>Cadmium free</li> <li>Good abrasion and kink resistance</li> <li>Ergonomic design</li> <li>High flexibility</li> <li>High resistance to acids and alkalis</li> <li>Low toxicity</li> <li>Lightweight – affording less operator fatigue</li> </ul>
SPECIFICATIONS	
Temperature range	-15°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of PCX hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Flexible PVC inner tube, reinforced with high tensile polyester nylon braid, covered with flexible PVC cover.
Applicable standards	ISO 5774:2016 BS EN ISO 6224:2011



### PCX – BLUE 30 METRE COILS



1350

PART NUMBER	mm	ins	mm	bar	PRICE per coil
PCX06	6.0	1/4	10.5	18	£61.92
PCX08	8.0	5/16	12.5	15	£74.39
PCX10	10.0	3/8	14.0	13	£79.07
PCX12	12.0	1/2	17.0	11	£106.77
PCX16	16.0	5/8	21.5	11	£209.22
PCX19	19.0	3/4	24.0	11	£262.57

### PCX – BLACK 30 METRE COILS



1350

PART NUMBER	mm	ins	mm	bar	PRICE per coil
PCX06BK	6.0	1/4	10.5	18	£61.92
PCX08BK	8.0	5/16	12.5	15	£74.39
PCX10BK	10.0	3/8	14.0	13	£79.07
PCX12BK	12.0	1/2	17.0	11	£106.77
PCX19BK	19.0	3/4	24.0	11	£262.57

## HIGH VISIBILITY HOSE

SUITABILITY	FEATURES
<ul style="list-style-type: none"> <li>Compressed air</li> <li>Water</li> <li>Chemicals</li> <li>Gas</li> </ul>	<ul style="list-style-type: none"> <li>High visibility for safety</li> <li>Good flexibility</li> <li>Silicone free</li> <li>Made from cadmium free materials</li> <li>Resistant to a wide range of chemicals</li> <li>High resistance to acids / alkalis</li> <li>Excellent abrasion resistance</li> </ul>
SPECIFICATIONS	
Temperature range	-15°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of reinforced PVC hose. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	White flexible PVC inner tube, reinforced with high tensile polyester nylon braid, covered with high visibility flexible PVC cover
Applicable standards	BS EN ISO 6224:2011
Hose marking	Part number & batch number



### PCX HIGH VISIBILITY – YELLOW 30 METRE COIL



1350

PART NUMBER	mm	ins	mm	bar	PRICE
PCX06HIVIZYEL	6	1/4	10.5	18	£68.09
PCX10HIVIZYEL	10	3/8	14.0	13	£85.73
PCX12HIVIZYEL	12	1/2	17.0	11	£117.40

### PCX HIGH VISIBILITY – PINK 30 METRE COIL



1350

PART NUMBER	mm	ins	mm	bar	PRICE
PCX06HVPNK	6	1/4	10.5	18	£68.09
PCX10HVPNK	10	3/8	14.0	13	£85.73
PCX12HVPNK	12	1/2	17.0	11	£117.40
PCX19HVPNK	19	3/4	24.0	11	£288.78

### PCX HIGH VISIBILITY – ORANGE 30 METRE COIL



1350

PART NUMBER	mm	ins	mm	bar	PRICE
PCX06HIVIZORA	6	1/4	10.5	18	£70.85
PCX10HIVIZORA	10	3/8	14.0	13	£79.04
PCX12HIVIZORA	12	1/2	17.0	11	£117.40
PCX19HVORA	19	3/4	24.0	11	£288.78