

SPECIFICATIONS

Operating pressure	0.8 to 16 bar (232 psi)
Operating temperature	-10°C to +60°C (14°F to 140°F)
Body & collet materials	Nickel plated brass
Threads	BSPP with PTFE sealing ring
Tube to connect	Nylon 6, 11, 12, polyurethane & polyethylene
Media	Compressed air

STUD COUPLING WITH SEALING RING BSPP MALE



2520

PART NUMBER	TUBE OD	THREAD
ZS6510041/8	4 mm	1/8" BSPP
ZS6510041/4	4 mm	1/4" BSPP
ZS6510051/8	5 mm	1/8" BSPP
ZS6510051/4	5 mm	1/4" BSPP
ZS6510061/8	6 mm	1/8" BSPP
ZS6510061/4	6 mm	1/4" BSPP
ZS6510081/8	8 mm	1/8" BSPP
ZS6510081/4	8 mm	1/4" BSPP
ZS6510083/8	8 mm	3/8" BSPP
ZS6510101/4	10 mm	1/4" BSPP
ZS6510103/8	10 mm	3/8" BSPP
ZS6510101/2	10 mm	1/2" BSPP
ZS6510121/4	12 mm	1/4" BSPP
ZS6510123/8	12 mm	3/8" BSPP
ZS6510121/2	12 mm	1/2" BSPP
ZS6510143/8	14 mm	3/8" BSPP
ZS6510141/2	14 mm	1/2" BSPP

STUD COUPLING WITH O-RING METRIC MALE



2520

PART NUMBER	TUBE OD	THREAD
Z651204M5	4 mm	M5
Z651204M6	4 mm	M6
Z651205M5	5 mm	M5
Z651206M5	6 mm	M5

BSPP MALE

PART NUMBER	TUBE OD	THREAD
Z6512041/8	4 mm	1/8" BSPP
Z6512041/4	4 mm	1/4" BSPP
Z6512061/8	6 mm	1/8" BSPP
Z6512061/4	6 mm	1/4" BSPP
Z6512081/8	8 mm	1/8" BSPP
Z6512081/4	8 mm	1/4" BSPP
Z6512083/8	8 mm	3/8" BSPP
Z6512101/4	10 mm	1/4" BSPP
Z6512103/8	10 mm	3/8" BSPP
Z6512121/4	12 mm	1/4" BSPP
Z6512123/8	12 mm	3/8" BSPP

STUD COUPLING METRIC FEMALE



2520

PART NUMBER	TUBE OD	THREAD
Z646304M5	4 mm	M5

BSPP FEMALE

PART NUMBER	TUBE OD	THREAD
Z6463041/8	4 mm	1/8" BSPP
Z6463051/8	5 mm	1/8" BSPP
Z6463061/8	6 mm	1/8" BSPP
Z6463061/4	6 mm	1/4" BSPP
Z6463081/8	8 mm	1/8" BSPP
Z6463081/4	8 mm	1/4" BSPP
Z6463101/4	10 mm	1/4" BSPP

EQUAL STRAIGHT CONNECTOR



2520

PART NUMBER	TUBE OD
Z658004	4 mm
Z658005	5 mm
Z658006	6 mm
Z658008	8 mm
Z658010	10 mm
Z658012	12 mm
Z658014	14 mm

BULKHEAD CONNECTOR



2520

PART NUMBER	TUBE OD
Z659004	4 mm
Z659005	5 mm
Z659006	6 mm
Z659008	8 mm
Z659010	10 mm
Z659012	12 mm
Z659014	14 mm

EQUAL ELBOW



2520

PART NUMBER	TUBE OD
Z655004	4 mm
Z655005	5 mm
Z655006	6 mm
Z655008	8 mm
Z655010	10 mm
Z655012	12 mm
Z655014	14 mm