

SPECIFICATIONS

Operating pressure	0.8 to 16 bar (232 psi)
Operating temperature	-10°C to +60°C (14°F to 140°F)
Body & collet materials	Nickel plated brass
Threads	BSPP with NBR O-ring
Tube to connect	Nylon 6, 11, 12, polyurethane & polyethylene
Media	Compressed air

STUD COUPLING WITH O-RING METRIC MALE



2520

PART NUMBER	TUBE OD	THREAD
Z651203M3	3 mm	M3
Z651203M5	3 mm	M5
Z651206M7	6 mm	M7

BSPP MALE

Z65120418M	4 mm	1/8" BSPP
Z65120618M	6 mm	1/8" BSPP
Z65120818M	8 mm	1/8" BSPP

SINGLE BANJO CONNECTOR METRIC MALE



2520

PART NUMBER	TUBE OD	THREAD
Z662103M3	3 mm	M3
Z662103M5	3 mm	M5

SWIVEL RUN TEE WITH O-RING METRIC MALE



2520

PART NUMBER	TUBE OD	THREAD
Z644203M3	3 mm	M3
Z644203M5	3 mm	M5

EQUAL STRAIGHT CONNECTOR



2520

PART NUMBER	TUBE OD
Z658003	3 mm

EQUAL ELBOW



2520

PART NUMBER	TUBE OD
Z655003	3 mm

Y CONNECTOR



2520

PART NUMBER	TUBE OD
Z65603	3 mm

PRESS FIT CARTRIDGE



2520

PART NUMBER	TUBE OD
Z67003	3 mm

STUD SWIVEL ELBOW WITH O-RING METRIC MALE



2520

PART NUMBER	TUBE OD	THREAD
Z652203M3	3 mm	M3
Z652203M5	3 mm	M5

SWIVEL BRANCH TEE WITH O-RING METRIC MALE



2520

PART NUMBER	TUBE OD	THREAD
Z643203M3	3 mm	M3
Z643203M5	3 mm	M5

SWIVEL Y CONNECTOR METRIC MALE



2520

PART NUMBER	TUBE OD	THREAD
Z645203M3	3 mm	M3
Z645203M5	3 mm	M5

BULKHEAD CONNECTOR



2520

PART NUMBER	TUBE OD
Z659003	3 mm

EQUAL TEE



2520

PART NUMBER	TUBE OD
Z654003	3 mm

STEM ADAPTOR



2520

PART NUMBER	TUBE OD	STEM OD
Z680003-04	3 mm	4 mm

NYLON BLANKING PLUG



2520

PART NUMBER	TUBE
Z69003	3 mm