

## NYLON 6:6 FITTINGS – BLUE

### FEATURES

Tefen hose fittings are the perfect choice to connect all types of flexible rubber & plastic tubes in domestic, industrial & all other general applications.

Main advantages:

- Strong & durable, highly impact resistant – all sizes are true outside diameter of the fittings, and will match Nylon 6:6 inside diameter of the tube. In order to secure tube on the fitting barb, it is recommended to use Tefen's snap clip or similar metal or plastic clip.
- How to use: push the tube onto the barb all the way to the stopper.
- Secure the tube tightly with a proper size snap clip.

### SPECIFICATIONS

Working pressure	Up to 14 bar (200 psi) at 20°C
Temperature range	-20°C to +110°C (-4°F to +230°F) subject to application
Colour	Blue
Material	Nylon 6:6

### CERTIFICATIONS & CONFORMITY



### STRAIGHT HOSETAIL BSPT MALE



3860

PART NUMBER	HOSE ID	THREAD	NUT AF
TF-46844028	4 mm	1/8" BSPT	11 mm
TF-46844048	4 mm	1/4" BSPT	14 mm
TF-46845028	5 mm	1/8" BSPT	11 mm
TF-46845048	5 mm	1/4" BSPT	14 mm
TF-46846028	6 mm	1/8" BSPT	11 mm
TF-46846048	6 mm	1/4" BSPT	14 mm
TF-46846068	6 mm	3/8" BSPT	17 mm
TF-46846088	6 mm	1/2" BSPT	22 mm
TF-46846128	6 mm	3/4" BSPT	27 mm
TF-46848028	8 mm	1/8" BSPT	11 mm
TF-46848048	8 mm	1/4" BSPT	14 mm
TF-46848068	8 mm	3/8" BSPT	17 mm
TF-46848088	8 mm	1/2" BSPT	22 mm
TF-46850048	10 mm	1/4" BSPT	14 mm
TF-46850068	10 mm	3/8" BSPT	17 mm
TF-46850088	10 mm	1/2" BSPT	22 mm
TF-46850128	10 mm	3/4" BSPT	27 mm
TF-46852048	12 mm	1/4" BSPT	14 mm
TF-46852068	12 mm	3/8" BSPT	17 mm
TF-46852088	12 mm	1/2" BSPT	22 mm
TF-46852128	12 mm	3/4" BSPT	27 mm
TF-46854068	14 mm	3/8" BSPT	17 mm
TF-46854088	14 mm	1/2" BSPT	22 mm
TF-46854128	14 mm	3/4" BSPT	27 mm
TF-46856088	16 mm	1/2" BSPT	22 mm
TF-46856128	16 mm	3/4" BSPT	27 mm
TF-46859088	19 mm	1/2" BSPT	22 mm
TF-46859128	19 mm	3/4" BSPT	27 mm
TF-6865168	25 mm	1" BSPT	36 mm



### SWIVEL STRAIGHT HOSETAIL BSPP FEMALE MAXIMUM TEMPERATURE 90°C



3860

PART NUMBER	HOSE ID	THREAD	NUT AF
TF-44644028	4 mm	1/8" BSPP	13 mm
TF-44644048	4 mm	1/4" BSPP	16 mm
TF-44645028	5 mm	1/8" BSPP	13 mm
TF-44645048	5 mm	1/4" BSPP	16 mm
TF-44645068	5 mm	3/8" BSPP	20 mm
TF-44646048	6 mm	1/4" BSPP	16 mm
TF-44646068	6 mm	3/8" BSPP	20 mm
TF-44646088	6 mm	1/2" BSPP	24 mm
TF-44648048	8 mm	1/4" BSPP	16 mm
TF-44648068	8 mm	3/8" BSPP	20 mm
TF-44648088	8 mm	1/2" BSPP	24 mm
TF-44648128	8 mm	3/4" BSPP	30 mm
TF-44650068	10 mm	3/8" BSPP	20 mm
TF-44650088	10 mm	1/2" BSPP	24 mm
TF-44650128	10 mm	3/4" BSPP	30 mm
TF-44652088	12 mm	1/2" BSPP	24 mm
TF-44652128	12 mm	3/4" BSPP	30 mm
TF-44654088	14 mm	1/2" BSPP	24 mm
TF-44654128	14 mm	3/4" BSPP	30 mm
TF-44656128	16 mm	3/4" BSPP	30 mm
TF-44659128	19 mm	3/4" BSPP	30 mm



### HOSETAIL



3860

PART NUMBER	HOSE ID
TF-46244008	4 mm
TF-46245008	5 mm
TF-46246008	6 mm
TF-46248008	8 mm
TF-46250008	10 mm
TF-46252008	12 mm
TF-46254008	14 mm
TF-46256008	16 mm
TF-46259008	19 mm



### REDUCING HOSETAIL



3860

PART NUMBER	HOSE ID	HOSE ID
TF-45645448	5 mm	4 mm
TF-45646448	6 mm	4 mm
TF-45646458	6 mm	5 mm
TF-45648458	8 mm	5 mm
TF-45648468	8 mm	6 mm
TF-45650468	10 mm	6 mm
TF-45650488	10 mm	8 mm
TF-45652488	12 mm	8 mm
TF-45652508	12 mm	10 mm
TF-45654508	14 mm	10 mm
TF-45654528	14 mm	12 mm
TF-45656528	16 mm	12 mm
TF-45656548	16 mm	14 mm
TF-45659548	19 mm	14 mm
TF-45659568	19 mm	16 mm