

SPECIFICATIONS	A700, A730, A760	A705	A740	A710, A720, A750
Max. pressure	10 bar (145 psi)	10 bar (145 psi)	12 bar (174 psi)	12 bar (174 psi)
Temperature range	-10°C to +80°C	-20°C to +150°C	-10°C to +80°C	-10°C to +80°C
Filtration threshold	50 µm	50 µm	36 µm	100 µm

**SILENCER
BRASS & SINTERED BRONZE
BSPP MALE**



1430

PART NUMBER	THREAD	DB LEVEL (6 BAR)
A700-1/8	1/8" BSPP	81
A700-1/4	1/4" BSPP	83
A700-3/8	3/8" BSPP	87
A700-1/2	1/2" BSPP	90
A700-3/4	3/4" BSPP	92 @ 4 bar
A700-1	1" BSPP	92 @ 4 bar

**SILENCER
BRASS & SINTERED BRONZE
METRIC MALE**



1430

PART NUMBER	THREAD
A730-M5	M5
A730-M7	M7

BSPP MALE

A730-1/8	1/8" BSPP
A730-1/4	1/4" BSPP
A730-3/8	3/8" BSPP
A730-1/2	1/2" BSPP
A730-3/4	3/4" BSPP
A730-1	1" BSPP

**ADJUSTABLE SILENCER
BRASS & SINTERED BRONZE
BSPP MALE**



1430

PART NUMBER	THREAD	LENGTH	
		MIN.	MAX.
A705-1/8	1/8" BSPP	25 mm	27 mm
A705-1/4	1/4" BSPP	28 mm	30 mm
A705-3/8	3/8" BSPP	33 mm	38 mm
A705-1/2	1/2" BSPP	39 mm	46 mm

**SILENCER
BRASS & SINTERED BRONZE
BSPP MALE**



1430

PART NUMBER	THREAD	DB LEVEL (6 BAR)
A740-1/8	1/8" BSPP	76
A740-1/4	1/4" BSPP	75
A740-3/8	3/8" BSPP	88
A740-1/2	1/2" BSPP	89
A740-3/4	3/4" BSPP	-

**SILENCER
BRASS & SINTERED BRONZE
BSPP MALE**



1430

PART NUMBER	THREAD	DB LEVEL (6 BAR)
A710-1/8	1/8" BSPP	73
A710-1/4	1/4" BSPP	74
A710-3/8	3/8" BSPP	85
A710-1/2	1/2" BSPP	89
A710-3/4	3/4" BSPP	90

**SILENCER WITH FLOW CONTROL
BRASS & SINTERED BRONZE
BSPP MALE**



1430

PART NUMBER	THREAD	DB LEVEL (6 BAR)
A750-1/8	1/8" BSPP	72
A750-1/4	1/4" BSPP	73
A750-3/8	3/8" BSPP	84
A750-1/2	1/2" BSPP	88

**SILENCER
BRASS & SINTERED BRONZE
METRIC MALE**



1430

PART NUMBER	THREAD	DB LEVEL (6 BAR)
A720-M5	M5	-

BSPP MALE

A720-1/8	1/8" BSPP	74
A720-1/4	1/4" BSPP	72
A720-3/8	3/8" BSPP	88
A720-1/2	1/2" BSPP	90
A720-3/4	3/4" BSPP	90
A720-1	1" BSPP	92

**SILENCER
BRASS & SINTERED BRONZE
METRIC TUBE CONNECTION**



1430

PART NUMBER	TUBE OD	TUBE ID
A760-M5	5 mm	3.0 mm
A760-4/2.7	4 mm	2.7 mm
A760-6/4	6 mm	4.0 mm