

SPECIFICATIONS	A770, A780	A712	A713, A714, A715
Max. pressure	6 bar (87 psi)	10 bar (145 psi)	10 bar (145 psi)
Temperature range	-10°C to +70°C	-10°C to +80°C	-10°C to +80°C
Filtration threshold	–	120 µm	50 µm

PAD SILENCER BRASS & SINTERED BRONZE BSPP MALE



1430

PART NUMBER	THREAD
A712-1/8	1/8" BSPP
A712-1/4	1/4" BSPP
A712-3/8	3/8" BSPP
A712-1/2	1/2" BSPP
A712-3/4	3/4" BSPP
A712-1	1" BSPP

Pad silencer with screwdriver slot

SILENCER BRASS & SINTERED BRONZE BSPT MALE



1430

PART NUMBER	THREAD
A713-1/8	1/8" BSPT
A713-1/4	1/4" BSPT
A713-3/8	3/8" BSPT
A713-1/2	1/2" BSPT
A713-3/4	3/4" BSPT
A713-1	1" BSPT

Silencer with filtering pad & screwdriver slot

SILENCER SINTERED BRONZE BSPP MALE



1430

PART NUMBER	THREAD
A714-1/8	1/8" BSPP
A714-1/4	1/4" BSPP
A714-3/8	3/8" BSPP
A714-1/2	1/2" BSPP
A714-3/4	3/4" BSPP
A714-1	1" BSPP

Silencer with screwdriver slot

SILENCER SINTERED BRONZE BSPP MALE



1430

PART NUMBER	THREAD
A715-1/8	1/8" BSPP
A715-1/4	1/4" BSPP
A715-3/8	3/8" BSPP
A715-1/2	1/2" BSPP
A715-3/4	3/4" BSPP
A715-1	1" BSPP

Silencer with hexagonal wrench

SILENCER ACETALIC RESIN, PLASTIC SOUNDPROOFING BSPP MALE



1430

PART NUMBER	THREAD	DB LEVEL (6 BAR)
A770-1/8	1/8" BSPP	87
A770-1/4	1/4" BSPP	84
A770-3/8	3/8" BSPP	90
A770-1/2	1/2" BSPP	90
A770-3/4	3/4" BSPP	91
A770-1	1" BSPP	90

SILENCER NYLON WITH FELT BSPP MALE



1430

PART NUMBER	THREAD	DB LEVEL (6 BAR)
A780-1/8	1/8" BSPP	87
A780-1/4	1/4" BSPP	90
A780-3/8	3/8" BSPP	92
A780-1/2	1/2" BSPP	92
A780-3/4	3/4" BSPP	92
A780-1	1" BSPP	–