

TUBE & HOSE SYMBOL GUIDE

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	Outside diameter millimetres		Wall thickness millimetres		Hose length metres		Burst pressure bar
	Inside diameter millimetres		Wall thickness inches		Bend radius millimetres		Vacuum pressure mm WG
	Outside diameter inches		Coil outside diameter inches		Thread size BSPP		Water pressure mH2O
	Inside diameter inches		Working length metres		Thread size BSPT		Colour
	Outside diameter of inner tube millimetres		Working length feet		Maximum pressure bar		Blow gun

HOSE ASSEMBLY & TEST FACILITY



Hydraulic Hose Assemblies

- 1 & 2 wire range 1/4" to 1" inclusive
- 4 wire spiral 1/4" to 1" inclusive
- PTFE smooth bore with stainless steel overbraid 1/4" to 1"
- PTFE convoluted with stainless steel overbraid 3/8" to 1"

Pneumatic Hose Assemblies

Ranging from 1/4" to 1" to suit customer requirements, plus air preparation assemblies

Sub-Assembly & Kit Supply

Breathing Air Assembly

Adheres to safety standards: TM14 BS EN 139:1995, BS EN 270:1994
BS EN 14593-1 & 2:2005, BS EN 14594:2005

Test Facility

We provide hydrostatic pressure testing to 10,000 psi & static pneumatic pressure testing to 600 psi