

connected

Ruggedness

EVERIS™ LQ6 SERIES, CHROME PLATED BRASS



800

800

800

FEATURES BENEFITS Non-spill design Redundant sealing when

- Disconnects under pressure with no spills
- Extra protection from leaks
 - Instant visual difference in cooling lines
- · Colour coding Valving system designed for extended periods of connect state • Friction-free valve
 - · Able to withstand long term, repeated use Eliminates tube kinking

Rotation allows movement

SPECIFICATIONS	
Pressure	Vacuum to 120 psi, 8.3 bar
Temperature	-17°C to +115°C (0°F to 240°F)
Spillage at 0 psi	0.03 cc / disconnect
Spillage at 120 psi	0.03 cc / disconnect
Main components	Chrome plated brass
Seal materials	EPDM
Spring	Stainless steel
Maximum flow at disconnect	4 gal/min, 15.1 l/min



COUPLING BODIES



PIPE THREAD - VALVED

NPT MALE - BLUE

PART NUMBER	THREAD
cLQ6D10006BLU	3/8" NPT



PIPE THREAD - VALVED NPT MALE - RED





IN-LINE - VALVED

BSPP MALE - BLUE

PART NUMBER	THREAD	
cLQ6D31006BLU	3/8" BSPP	
cl Q6D31008BLU	1/2" BSPP	



BSPP MALE - RED

PART NUMBER	THREAD
cLQ6D31006RED	3/8" BSPP
cLQ6D31008RED	1/2" BSPP



IN-LINE - VALVED

HOSE BARB - BLUE

PART NUMBER	TUBE ID	METRIC EQ.
cLQ6D17006BLU	3/8"	9.5 mm
cLQ6D17008BLU	1/2"	12.7 mm

IN-LINE – VALVED

HOSE BARB - RED

PART NUMBER	TUBE ID	METRIC EQ.
cLQ6D17006RED	3/8"	9.5 mm
cLQ6D17008RED	1/2"	12.7 mm



IN-LINE - VALVED

SAE MALE - BLUE

PART NUMBER	THREAD	
cLQ6D30006BLU	3/8" SAE-6	
cLQ6D30008BLU	1/2" SAE-8	

IN-LINE - VALVED

SAE MALE - RED

· · · · · · · · · · · · · · · · · · ·			
	PART NUMBER	THREAD	
	cLQ6D30006RED	3/8" SAE-6	
	cLQ6D30008RED	1/2" SAE-8	



IN-LINE - VALVED

FERRULESS POLYTUBE

FITTING, PTF - BLUE

PART NUMBER	TUBE OD	TUBE ID	METRIC EQ.	
cLQ6D13008BLU	1/2"	3/8"	12.7 x 9.5 mm	

IN-LINE - VALVED FERRULESS POLYTUBE

FITTING, PTF - RED

PART NUMBER	TUBE OD	TUBE ID	METRIC EQ.	
cLQ6D13008RED	1/2"	3/8"	12.7 x 9.5 mm	

