

EUROLON PAINT & FLUID HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Solvents Chemicals Paint 	<ul style="list-style-type: none"> Fully flexible at low temperatures Paint & solvent resistant High burst pressures Highly abrasion resistant Non-conductive Light Easy to clean Durable
SPECIFICATIONS	
Temperature range	-40°C to +75°C
Pressure rating	Values given are based on the short term burst pressure of PEPS hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	PA12 nylon inner with polyurethane middle layer, reinforced with high tensile polyester braid & polyurethane outer cover.
Applicable standards	BS EN ISO 1307



PEPS – GREEN 30 METRE COILS

PART NUMBER				
PEPS 06	6.3	1/4	11.5	20
PEPS 10	9.5	3/8	15.5	15



1352

AQUAVEND REINFORCED PVC HOSE – PHR SERIES

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Food Water Chemicals Gas Fuel / oil 	<ul style="list-style-type: none"> Made from cadmium free materials Silicone free Mirror smooth inner for improved flow Extruded with brilliant white finish Resistance to a wide range of chemicals Good flexibility Excellent abrasion resistance Good kink resistance Will not support microbiological growth WRAS approved construction – certification available on request PVCs FDA approved
SPECIFICATIONS	
Temperature range	-15°C to +70°C
Pressure rating	Values given are based on the short term burst pressure of PHR hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Hytrell inner tube. High quality PVC material. Braided with polyester fibre.
Independently tested in accordance with BS6920	

PHR – WHITE 30 METRE COILS

PART NUMBER			
PHR06	6.3	12.0	20
PHR10	10.0	16.0	15
PHR12	12.5	19.0	11
PHR19	19.0	26.0	10
PHR25	25.0	33.0	8



1352

Coils can be cut in multiples of 5 metres
subject to a 25% surcharge



TRICOFLEX® FLEXIBLE PVC WATER HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Irrigation Water supply & delivery 	<ul style="list-style-type: none"> Highly flexible for easy handling Excellent resistance to repeated bending, crushing & pulling Good resistance against abrasion & UV rays
SPECIFICATIONS	
Temperature range	-15°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of Tricoflex hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Exterior covering in ultra UV resistant PVC. With woven polyester fibre reinforcement & two-layer smooth lining.

TRICOFLEX® – YELLOW 25 METRE COILS

PART NUMBER				
TRI-117135	12.5	1/2	18.0	8
TRI-116887	19.0	3/4	25.5	8
TRI-048273	25.0	1	32.5	8



1365

50 METRE COILS

TRI-117151	12.5	1/2	18.0	8
TRI-051546	19.0	3/4	25.5	8
TRI-048374	25.0	1	32.5	8

100 METRE COILS

TRI-117016	12.5	1/2	18.0	8
TRI-054437	19.0	3/4	25.5	8
TRI-048363	25.0	1	32.5	8