

## RAUFILAM SLIDETEC REINFORCED SOFT PVC HOSE

### SUITABILITY

- Compressed air supply for pneumatic tools
- Fixed or mobile winding devices for compressed air supply
- Installation companies
- Repair workshops (cars / utility vehicles)
- Carpenters workshops

### FEATURES / BENEFITS

- Exclusive hose surface with easy-slide technology for unrivalled tactile characteristics & convenient handling
- Exceptionally high flexibility
- Made of high-quality environmentally friendly PVC materials
- TÜV-tested
- High resistance against chemicals
- Abrasion-resistant & resistant to ageing
- High reinforcement density
- Phthalate-free

### OTHER CONFORMITIES

- REACH regulation (EC) no. 1907/2006 (no SVHC)
- RoHS electrical & electronic equipment directive 2011/65/EU including the supplements to the delegated directive 2015/863
- End-of-life vehicle directive 2000/53/EC & 2002/525/EC
- WEEE waste electrical & electronic equipment directive 2012/19/EU

### SPECIFICATIONS

Temperature range	-20°C to +60°C
Pressure ratings	Values given are based on the hose at 20°C
Construction	Black RAU-PVC 7059 inner layer. Pressure carrier made of high-quality polyester fabric. Sky blue RAL5015, RAU-PVC 6558 sheathing.



Phthalate free & RoHS 3 compliant

New



## RAUFILAM SLIDETEC – BLUE 50 METRE COILS

1320

PART NUMBER				
REH10290331001	6.0	1/4	11.0	20
REH10290341001	8.0	5/16	13.0	20
REH10290351001	9.0	3/8	14.6	20
REH10290361001	10.0	3/8	16.0	20
REH10290371001	12.7	1/2	18.7	20
REH10290661001	16.0	5/8	22.6	20
REH10290471001	19.4	3/4	26.8	20
REH10290531001	25.4	1	34.0	15

## RAUAQUA T-FLEX REINFORCED PVC HOSE

### SUITABILITY

- Food category A, B, C and D1
- Acidic foods with a pH below 4.5
- Alcoholic foods with an alcohol content up to 50 %
- Examples: water, tea, coffee, lemonade, soft drinks, energy drinks, beer, wine and clear simple or concentrated fruit or vegetable juices, milk, yoghurt.

### FEATURES / BENEFITS

- Multi-layer hose for use in drinking water & food applications
- Meets the strict requirements of the UBA for products in contact with drinking water
- Tested according to KTW-BWGL (Annex E) for cold and hot water & DIN EN 16421:2015-05
- Absolutely opaque, therefore counteracts the formation of dangerous microbes & algae
- UV-resistant and resistant to standard cleaning and disinfection agents (based on DVGW W319 and W291)

### OTHER CONFORMITIES

RAUAQUA T-Flex and the polymer materials RAU-SRT 320 and RAU-SRT 620 used for the production complies with Regulation (EC) no. 1935/2004 and with Regulation (EU) no. 10/2011 on materials and objects intended to come into contact with foodstuffs.

### SPECIFICATIONS

Temperature range	-30°C to +70°C (-22°F to +158°F)
Pressure ratings	Values given are based on the hose at 20°C
Construction	Blue reinforced hose made of RAU-SRT320 and RAU-SRT620

### OTHER INFORMATION

RAUAQUA T-Flex is **not** suitable for contact with foods that are assigned to food category D2. REHAU RAUAQUA T-Flex is also **not** suitable for contact with fatty foods containing free fats on the surface.

New



## RAUAQUA T-FLEX – BLUE 25 METRE COILS

1320

PART NUMBER				
REH10049011001	12.8	1/2	18.8	15
REH10049021001	19.0	3/4	25.0	15

  

PART NUMBER				
REH10049011002	12.8	1/2	18.8	15
REH10049031001	19.0	3/4	25.0	15

