

## FLEXELENE™ 66E TUBING

### FEATURES / BENEFITS

- Flexelene™ FLX66E is part of the Flexelene™ E Series
- 66 Shore A hardness and a flexible non-allergenic TPE Alloy
- Provides a biocompatible fluid surface with ultra-low extractables / leachables making this tubing suitable for neonatal medical applications
- Meant to withstand peristaltic pumping action
- PVC-free with no DEHP or phthalates

### SPECIFICATIONS

Pressure rating	Values given are based on the short term burst pressure of Flexelene™ hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Hardness	Shore A 66
Construction	TPE alloy

Supplied in full coils only



New

### FLEXELENE™ 66E – CLEAR 15 METRE COILS

701

#### PART NUMBER

EJ-FLX66E1-2	1/8	1/16
EJ-FLX66E1.5-2.5	5/32	3/32
EJ-FLX66E2-4	1/4	1/8
EJ-FLX66E3-5	5/16	3/16
EJ-FLX66E4-6	3/8	1/4
EJ-FLX66E5-7	7/16	5/16
EJ-FLX66E6-8	1/2	3/8
EJ-FLX66E8-12	3/4	1/2



## FLEXELENE™ SFX TUBING

### FEATURES / BENEFITS

- Flexelene™ SFX is an economical, flexible polyolefin tubing that features low extractables
- Exhibiting excellent heat-sealing properties and meeting USP Class VI requirements make it an ideal tubing for biomedical and pharmaceutical purposes
- Materials contain no PVC, DEHP phthalates, or other plasticisers

### SPECIFICATIONS

Hardness	Shore A 73
Construction	Flexible polyolefin tubing

Supplied in full coils only



New

### FLEXELENE™ SFX – CLEAR 30 METRE COILS

701

#### PART NUMBER

EJ-SFX1-2	1/8	1/16	3.97
EJ-SFX1.5-2.5	5/32	3/32	3.04
EJ-SFX2-4	1/4	1/8	3.34
EJ-SFX3-5	5/16	3/16	2.77
EJ-SFX4-6	3/8	1/4	1.93
EJ-SFX5-7	7/16	5/16	1.81
EJ-SFX6-8	1/2	3/8	1.63
EJ-SFX8-12	3/4	1/2	1.94



## EJ PRENE™ TPV PERISTALTIC PUMP TUBING

### FEATURES / BENEFITS

- Designed for peristaltic pump applications and offers durability with excellent pump life by reducing production downtime due to tube failure
- Flexible and lightweight, possesses very good chemical compatibility, and can be used in a wide range of applications
- This high-performance elastomer exhibits similar properties to rubber and is the first choice as an alternative to Santoprene™
- Full BPOG standardised extractables test results are available on request

### SPECIFICATIONS

Hardness	Shore A 70
Construction	Thermoplastic vulcanisate (TPV) tubing

Available in multiple of 1 m lengths. A 25% surcharge applies.  
Please contact your distributor for further information.



New

### EJ PRENE™ – NATURAL 15 METRE COILS

701

#### PART NUMBER

EJ-EJP5-1.5	3/32	1/32
EJ-EJP1-2	1/8	1/16
EJ-EJP1.5-2.5	5/32	3/32
EJ-EJP2-3	3/16	1/8
EJ-EJP3-4	1/4	3/16
EJ-EJP6-8	1/2	3/8

