

LIGHTWEIGHT DELIVERY HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> • Light pressure transfer of liquids, slurries & powders • Agricultural • Horticultural • Marine • Construction 	<ul style="list-style-type: none"> • Lightweight construction for easy handling • Optimum flow is maintained by the smooth bore • Tough, flexible & extremely durable • Retains flexibility, even in cold weather applications • Outstanding resistance to the effects of weather • Excellent chemical & abrasion resistance • RoHS 3 compliant.
SPECIFICATIONS	
Temperature range	-15°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of lightweight medium duty suction discharge hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	White rigid crush resistant anti-shock PVC spiral helix encapsulated in a flexible translucent green PVC cover, with a smooth inside wall.
Colour	Transparent green, white helix

Supplied in full coils only



Phthalate free & RoHS 3 compliant


**LIGHTWEIGHT HOSE
5 METRE COILS**


6970

PART NUMBER					
H-LWDH100-5	25.4	32.0	114	8.0	7
H-LWDH125-5	32.0	39.2	143	7.0	7
H-LWDH150-5	38.0	45.4	171	6.5	7
H-LWDH200-5	51.6	59.8	230	6.0	7
H-LWDH250-5	63.5	71.9	284	5.0	7
H-LWDH300-5	76.0	86.4	342	4.0	7

10 METRE COILS

H-LWDH100-10	25.4	32.0	114	8.0	7
H-LWDH125-10	32.0	39.2	143	7.0	7
H-LWDH150-10	38.0	45.4	171	6.5	7
H-LWDH200-10	51.6	59.8	230	6.0	7
H-LWDH250-10	63.5	71.9	284	5.0	7
H-LWDH300-10	76.0	86.4	342	4.0	7

30 METRE COILS

H-LWDH100-30	25.4	32.0	114	8.0	7
H-LWDH125-30	32.0	39.2	143	7.0	7
H-LWDH150-30	38.0	45.4	171	6.5	7
H-LWDH200-30	51.6	59.8	230	6.0	7
H-LWDH250-30	63.5	71.9	284	5.0	7
H-LWDH300-30	76.0	86.4	342	4.0	7

Sizes above 51 mm will incur an extra carriage charge
Please contact your distributor for further information

MEDIUM DUTY SUCTION & DELIVERY HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> • Industrial • Suction & discharge of water, sewage, slurries & powders • Agricultural • Construction 	<ul style="list-style-type: none"> • Tough, extremely durable with excellent flexibility • Optimum flow is maintained by the smooth bore • Flexibility maintained even under cold weather conditions • Outstanding resistance to the effects of weather • Excellent chemical & abrasion resistance • RoHS 3 compliant
SPECIFICATIONS	
Temperature range	-10°C to +55°C
Pressure rating	Values given are based on the short term burst pressure of lightweight medium duty suction discharge hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	White rigid, crush & kink resistant anti-shock PVC spiral helix encapsulated in the industry standard olive green flexible PVC cover & smooth inside wall to reduce friction.
Colour	Olive green, white helix

Supplied in full coils only



Phthalate free & RoHS 3 compliant


**MEDIUM DUTY HOSE
10 METRE COILS**


6970

PART NUMBER					
H-MDSL100-10	25.4	31.8	57	8.0	8
H-MDSL125-10	32.0	39.0	72	7.0	8
H-MDSL150-10	38.0	45.8	86	6.3	8
H-MDSL200-10	51.6	60.2	114	5.3	8
H-MDSL250-10	63.5	73.1	143	5.0	8
H-MDSL300-10	76.0	86.0	171	4.0	8
H-MDSL400-10	102.0	113.0	284	4.0	8

30 METRE COILS

H-MDSL100-30	25.4	31.8	57	8.0	8
H-MDSL125-30	32.0	39.0	72	7.0	8
H-MDSL150-30	38.0	45.8	86	6.3	8
H-MDSL200-30	51.6	60.2	114	5.3	8
H-MDSL250-30	63.5	73.1	143	5.0	8
H-MDSL300-30	76.0	86.0	171	4.0	8
H-MDSL400-30	102.0	113.0	284	4.0	8

Sizes above 51 mm will incur an extra carriage charge
Please contact your distributor for further information