

OIL RESISTANT SUCTION & DELIVERY HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> • Transportation: fuels & oils 	<ul style="list-style-type: none"> • Resistant to a wide range of fuels & oils • Tough, flexible & durable even under very cold working conditions • Constructed for higher vacuums & pressures • Minimum frictional loss is achieved by the smooth bore • RoHS 3 compliant
SPECIFICATIONS	
Temperature range	-10°C to +55°C
Pressure rating	Values given are based on the short term burst pressure of lightweight medium duty suction discharge hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	White rigid crush & kink resistant anti-shock PVC spiral helix encapsulated in the industry standard blue flexible oil resistant PVC cover, with a smooth inside wall.
Colour	Blue, white helix

Supplied in full coils only



6970

**MEDIUM DUTY FUEL & OIL HOSE
5 METRE COILS**

PART NUMBER					
H-MDOR100-5	25.4	33.8	113	9.3	9
H-MDOR125-5	32.0	40.8	144	8.0	9
H-MDOR150-5	38.0	47.0	171	8.0	9
H-MDOR200-5	51.6	60.9	230	7.3	9

10 METRE COILS

H-MDOR100-10	25.4	33.8	113	9.3	9
H-MDOR125-10	32.0	40.8	144	8.0	9
H-MDOR150-10	38.0	47.0	171	8.0	9
H-MDOR200-10	51.6	60.9	230	7.3	9
H-MDOR300-10	76.0	87.6	342	6.0	9
H-MDOR400-10	102.0	115.5	459	4.7	9

30 METRE COILS

H-MDOR100-30	25.4	33.8	113	9.3	9
H-MDOR125-30	32.0	40.8	144	8.0	9
H-MDOR150-30	38.0	47.0	171	8.0	9
H-MDOR200-30	51.6	60.9	230	7.3	9
H-MDOR300-30	76.0	87.6	342	6.0	9
H-MDOR400-30	102.0	115.5	459	4.7	9

Sizes above 51 mm will incur an extra carriage charge
Please contact your distributor for further information

FOOD GRADE SUCTION & DELIVERY HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> • Food industry 	<ul style="list-style-type: none"> • EN No 10/2011 Compliant for food contact applications • Lightweight for easy handling • Transparent for easy visibility • Remains flexible, even in colder conditions • Excellent chemical & abrasion resistance • NSF51 & NSF61 approved for the transfer of drinking water • RoHS 3 compliant
SPECIFICATIONS	
Temperature range	-40°C to +80°C
Pressure rating	Values given are based on the short term burst pressure of lightweight medium duty suction discharge hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	White rigid crush & kink resistant anti-shock PVC spiral helix encapsulated in a transparent flexible FDA approved PVC cover, with a smooth inside wall.
Colour	Transparent, white helix

Supplied in full coils only



6970

**LIGHTWEIGHT HOSE
10 METRE COILS**

PART NUMBER					
H-FDH100-10	25.4	32.0	114	8.0	7
H-FDH125-10	32.0	39.2	143	7.0	7
H-FDH150-10	38.0	45.4	171	6.5	7
H-FDH200-10	51.6	59.8	230	6.0	7
H-FDH300-10	76.0	86.4	342	4.0	7

30 METRE COILS

H-FDH100-30	25.4	32.0	114	8.0	7
H-FDH125-30	32.0	39.2	143	7.0	7
H-FDH150-30	38.0	45.4	171	6.5	7
H-FDH200-30	51.6	59.8	230	6.0	7
H-FDH300-30	76.0	86.4	342	4.0	7

Sizes above 51 mm will incur an extra carriage charge
Please contact your distributor for further information