

LOUISIANA INDUSTRIAL WATER SUCTION & DELIVERY HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Irrigation, suction & delivery of fertilisers, insecticides, acid solutions & detergents 	<ul style="list-style-type: none"> Smooth inside surface, light corrugated exterior Easy handling, light & flexible Good resistance to temperature, abrasion, crushing, atmospheric agents & chemical attack.
SPECIFICATIONS	
Temperature range	-5°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of Louisiana industrial water delivery hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Flexible PVC wall reinforced with a shockproof rigid PVC spiral
Colour	Translucent green with ivory spiral

Supplied in full coils only

LOUISIANA INDUSTRIAL 30 METRE COILS



6970

PART NUMBER					
H-WDH075-30	19.0	3/4	24.0	8.0	7
H-WDH100-30	25.0	1	31.0	8.0	7
H-WDH125-30	32.0	1 1/4	38.0	7.0	7
H-WDH150-30	38.0	1 1/2	45.0	6.5	7
H-WDH200-30	51.0	2	59.0	6.0	7

LOUISIANA FOOD QUALITY SUCTION & DELIVERY HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> PVC hose with rigid PVC spiral, for delivery & suction of food liquids Suitable for use with food according to Reg. CE 1935/2004 & Reg. UE 10/2011 	<ul style="list-style-type: none"> Smooth surface Light & flexible Good resistance to temperature, abrasion, crushing, atmospheric agents & chemical attack.
SPECIFICATION	
Temperature range	-5°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of Louisiana food quality delivery hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Flexible PVC wall reinforced with a shockproof rigid PVC spiral
Colour	Translucent yellow with ivory spiral

Supplied in full coils only

LOUISIANA FOOD QUALITY 30 METRE COILS



6970

PART NUMBER					
H-LFQDH075-30	20	3/4	26.2	8.0	7
H-LFQDH100-30	25	1	31.6	8.0	7
H-LFQDH125-30	32	1 1/4	39.2	7.0	7
H-LFQDH150-30	38	1 1/2	45.4	6.5	7
H-LFQDH200-30	50	2	58.2	6.0	7




OREGON GENERAL PURPOSE VACUUM HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> PVC hose with rigid PVC spiral, for suction & ducting of air, fumes, chips, dusts, textile filaments & ventilation 	<ul style="list-style-type: none"> Flexible & lightweight Resistant to most oxidising & reducing agents & dilute acids & alkalis Good resistance to temperature, abrasion, crushing, atmospheric agents & chemical attack.
SPECIFICATIONS	
Temperature range	-10°C to +60°C
Construction	Flexible PVC wall reinforced with a shockproof rigid PVC spiral
Colour	Grey
Self extinguishing	UL94 V2

Supplied in full coils only

OREGON VACUUM 50 METRE COILS



6970

PART NUMBER				
H-GVH100	25	1	30.6	5
H-GVH125	32	1 1/4	38.2	5
H-GVH150	38	1 1/2	44.4	5
H-GVH200	51	2	57.4	4