



## METALFLEX INDUSTRIAL WIRE REINFORCED SUCTION & DELIVERY HOSE

SUITABILITY		FEATURES / BENEFITS				
Soft PVC hose with embedded steel spiral suction of industrial liquids		Smooth surface     Light & flexible     Good resistance to temperature, abrasion, crushing, atmospheric agents & chemical attack				
SPECIFICATIONS						
Temperature range	-5°C to +65°C					
Pressure rating	Values given are based on the short term burst pressure of Metalflex industrial wire reinforced suction discharge hose at 20°C using a 3:1 safety factor.  NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.					
Construction	Flexible PVC inner hose with a steel spiral					
Colour	Clear					
	Suppli	ed in full coils only				

New Additions  METALFLEX 60 METRE COILS	i	UU	® WERLETT ME	THEREX I DA	DAM PROE INTERLY		6970		
PART NUMBER		(Ins	$\Theta$	(1)					
H-MIWRSH010-60	10	3/8	15.5	7.0	8.5				
H-MIWRSH012-60	12	1/2	17.5	7.0	8.5				
H-MIWRSH016-60	16	5/8	21.5	6.0	8.5				
H-MIWRSH020-60	20	3/4	26.5	5.0	8.5				
H-MIWRSH025-60	25	1	32.0	5.0	8.5				
H-MIWRSH032-60	32	1 1/4	40.0	4.5	8.5				
30 METRE COILS									
H-MIWRSH038-30	38	1 1/2	46.0	4.0	8.5				
H-MIWRSH050-30	50	2	59.0	3.0	8.0				

## ARMORVIN HNA WIRE REINFORCED FOOD QUALITY SUCTION & DELIVERY HOSE

AKINOKVIN HINA	WILE	KEINFORGED FOOD QUALITY 30			
SUITABILITY		FEATURES / BENEFITS			
Soft PVC hose with embedded galvanised steel spiral, for suction & delivery of food liquids, alcoholic food liquids up to 50% & milk products		Lightweight, strong & bendable Smooth inside & outside Good resistance to temperature, abrasion, crushing, atmospheric agents & chemical attack.			
SPECIFICATIONS					
Temperature range	-5°C to +65°C				
Pressure rating	Values given are based on the short term burst pressure of Armorvin HNA wire reinforced suction discharge hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.				
Construction	Soft PVC hose with embedded steel wire reinforcement				
Colour	Clear				
U"	Supp	lied in full coils only			



XI

Sizes above 51 mm will incur an extra carriage charge Please contact your distributor for further information

114

102



P-AM102-30