

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> <li>• Chemicals</li> <li>• Water</li> <li>• Fuel</li> <li>• Oil</li> </ul>	<ul style="list-style-type: none"> <li>• For use with push-in fittings</li> <li>• Superior flexibility with excellent memory</li> <li>• Kink &amp; abrasion resistant</li> <li>• Low gas permeability, extractables &amp; compression set</li> <li>• Resistant to chemicals, water, fuel, oil &amp; fungus</li> <li>• Suitable for vacuum</li> </ul>
SPECIFICATIONS	
Temperature range	-40°C to +74°C
Pressure rating	Values given are based on the short term burst pressure of Fre-thane 85A PU tube at 20°C using a 3:1 safety factor.
Vacuum 28" Hg	NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Ether based polyurethane. Suitable for use with water.
Base resin compliance	NSF61, Meets UL94HB, USPVI



Supplied in full coils only

**CO-1J BLACK**  
15 METRE COILS



2010

PART NUMBER			
CO-1J-01301	1/8	0.066	9
CO-1J-02501	1/4	1/8	10

**CO-1J CLEAR**  
15 METRE COILS



2010

PART NUMBER			
CO-1J-01310	1/8	0.066	9
CO-1J-02510	1/4	1/8	10

**30 METRE COILS**

CO-1J-01510	3/8	1/4	6
-------------	-----	-----	---

**CO-1J TRANSLUCENT RED**  
15 METRE COILS



2010

PART NUMBER			
CO-1J-01325	1/8	0.066	9
CO-1J-02525	1/4	1/8	10

**30 METRE COILS**

CO-1J-01525	3/8	1/4	6
-------------	-----	-----	---

**CO-1J TRANSLUCENT GREEN**  
15 METRE COILS



2010

PART NUMBER			
CO-1J-01326	1/8	0.066	9
CO-1J-02526	1/4	1/8	10

**CO-1J TRANSLUCENT BLUE**  
15 METRE COILS



2010

PART NUMBER			
CO-1J-01327	1/8	0.066	9
CO-1J-02527	1/4	1/8	10

**30 METRE COILS**

CO-1J-01527	3/8	1/4	6
-------------	-----	-----	---

**CO-1J TRANSLUCENT YELLOW**  
15 METRE COILS



2010

PART NUMBER			
CO-1J-01328	1/8	0.066	9
CO-1J-02528	1/4	1/8	10