


SUITABILITY	FEATURES / BENEFITS			
<ul style="list-style-type: none"><li>• Compressed air</li><li>• Vacuum</li><li>• Chemicals</li><li>• Oil</li><li>• Water</li></ul>	<ul style="list-style-type: none"><li>• Flexible &amp; lightweight</li><li>• Good abrasion resistance</li><li>• Excellent memory</li><li>• Excellent air, water, oil &amp; chemical resistance</li><li>• Easy to assemble &amp; replace ends</li></ul>			
SPECIFICATIONS				
Temperature range	-55°C to +60°C			
Pressure rating	Vacuum -28 Hg			
	Values given are based on the short term burst pressure of PS hose at 20°C using a 3:1 safety factor.			
	NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.			
	8 x 5 mm	10 x 6.5 mm	12 x 8 mm	16 x 11 mm
	12 bar	10 bar	10 bar	10 bar
Construction	Ether based polyurethane, brass BSPT male swivel fittings are nickel plated with pre-applied thread sealant. 98 A shore.			



## PS YELLOW – WITH BSPT SWIVEL FITTING

25.4 MM MANDREL SIZE

1110

PART NUMBER				
PS-08-2MY	8	5.0	2	1/4
PS-08-4MY	8	5.0	4	1/4
PS-08-6MY	8	5.0	6	1/4

31.8 MM MANDREL SIZE

PS-10-2MY	10	6.5	2	1/4
PS-10-4MY	10	6.5	4	1/4
PS-10-6MY	10	6.5	6	1/4

42.3 MM MANDREL SIZE

PS-12-2MY	12	8.0	2	3/8
PS-12-4MY	12	8.0	4	3/8
PS-12-6MY	12	8.0	6	3/8



## PS RED – WITH BSPT SWIVEL FITTING

25.4 MM MANDREL SIZE

1110

PART NUMBER				
PS-08-2MR	8	5.0	2	1/4
PS-08-4MR	8	5.0	4	1/4
PS-08-6MR	8	5.0	6	1/4

31.8 MM MANDREL SIZE

PS-10-2MR	10	6.5	2	1/4
PS-10-4MR	10	6.5	4	1/4
PS-10-6MR	10	6.5	6	1/4

42.3 MM MANDREL SIZE

PS-12-2MR	12	8.0	2	3/8
PS-12-4MR	12	8.0	4	3/8
PS-12-6MR	12	8.0	6	3/8



## PS BLUE – WITH BSPT SWIVEL FITTING

25.4 MM MANDREL SIZE

1110

PART NUMBER				
PS-08-2MB	8	5.0	2	1/4
PS-08-4MB	8	5.0	4	1/4
PS-08-6MB	8	5.0	6	1/4

31.8 MM MANDREL SIZE

PS-10-2MB	10	6.5	2	1/4
PS-10-4MB	10	6.5	4	1/4
PS-10-6MB	10	6.5	6	1/4

42.3 MM MANDREL SIZE

PS-12-2MB	12	8.0	2	3/8
PS-12-4MB	12	8.0	4	3/8
PS-12-6MB	12	8.0	6	3/8

76.2 MM MANDREL SIZE

PS-16-2MB	16	11.0	2	1/2
PS-16-4MB	16	11.0	4	1/2
PS-16-6MB	16	11.0	6	1/2



## Do you also need?

### ATP technibond polyurethane tubing

An efficient & attractive way to colour code your tubing runs. Bonded tubing allows for quicker installation time of multiple lines by eliminating costly repetition & vinyl sleeving.

Harness all your air, oil, water & electrical needs into one complete, colour-coded package.



Please contact your distributor for further information