

SPIRAL POLYURETHANE TUBE

SUITABILITY	FEATURES / BENEFITS
• Compressed air	<ul style="list-style-type: none"> • Light & flexible • Low friction • Excellent resistance to oil, solvent & other non-aqueous solutions • Excellent recoil ability & crimp resistance • Long service life with outstanding ageing qualities • Excellent abrasion resistance

SPECIFICATIONS	
Temperature range	-30°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of CEJN spiral hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Ester based, non-braided polyurethane.

SPIRAL – BLUE

42 CM MANDREL SIZE



285

PART NUMBER				
C19958B5820	5.0	8	2	10
C19958B5840	5.0	8	4	10
C19958B5860	5.0	8	6	10
C19958B5880	5.0	8	8	10

SPIRAL – BLUE

65 CM MANDREL SIZE



285

PART NUMBER				
C19958B6220	8	12	2	10
C19958B6240	8	12	4	10
C19958B6260	8	12	6	10
C19958B6280	8	12	8	10

52 CM MANDREL SIZE

C19958B6020	6.5	10	2	10
C19958B6040	6.5	10	4	10
C19958B6060	6.5	10	6	10
C19958B6080	6.5	10	8	10

95 CM MANDREL SIZE

C19958B6620	11	16	2	10
C19958B6640	11	16	4	10
C19958B6660	11	16	6	10
C19958B6680	11	16	8	10

POLYURETHANE AIRLINE RECOILS

SUITABILITY	FEATURES / BENEFITS
• Compressed air	<ul style="list-style-type: none"> • Light & flexible • Low friction hose • Excellent resistance to oil, solvent & other non-aqueous solutions • Excellent recoil ability & crimp resistance • Long service life with outstanding ageing qualities • Excellent abrasion resistance • Also available in 300, 310, 315, 320 & 410 series

SPECIFICATIONS	
Temperature range	-30°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of CEJN PU hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Spiral polyurethane. Ester-based, non-braided polyurethane. Assembled with streamline couplings, nipples & swivels.



285

HOSE KITS – BLUE

SPIRAL HOSE WITH BSPT FIXED ADAPTORS

PART NUMBER					
C199589325	5.0	8	2	16	1/4
C199589987	6.5	10	2	16	1/4
C199589988	6.5	10	4	16	1/4
C199589805	8.0	12	4	16	3/8
C199589885	11.0	16	4	16	1/2
C199589955	6.5	10	6	16	1/4
C199589804	8.0	12	6	16	3/8
C199589801	8.0	12	8	16	3/8
C199589862	11.0	16	8	16	1/2



285

HOSE KITS – BLUE

SPIRAL HOSE WITH BSPT SWIVEL ADAPTORS

PART NUMBER					
C199589978	5.0	8	2	16	1/4
C199589947	6.5	10	2	16	1/4
C199589997	8.0	12	2	16	3/8
C199589965	5.0	8	4	16	1/4
C199589949	6.5	10	4	16	1/4
C199589967	8.0	12	4	16	3/8
C199589810	11.0	16	4	16	1/2
C199589954	6.5	10	6	16	1/4
C199589998	8.0	12	6	16	3/8
C199589957	6.5	10	8	16	1/4
C199589809	8.0	12	8	16	3/8
C199589346	11.0	16	8	16	1/2