

SPIRAL ANTI-SPARK POLYURETHANE TUBE

SUITABILITY

- Welding environments
- Assembly lines, fixed workplaces
- Breathing air applications

FEATURES / BENEFITS

- Low friction
- Spark & scorch resistant
- Excellent resistance to oils, solvents & other non-aqueous solutions
- Long service life with outstanding ageing qualities
- Excellent recoil ability

SPECIFICATIONS

Temperature range	-30°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of CEJN spiral anti-spark hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Ester based polyurethane.
Applicable standards	EN14594:2005 when used with approved breathing air filters.



SPIRAL ANTI-SPARK 3 3/8" MANDREL SIZE



285

PART NUMBER



C199584020	6.5	10	2	10
C199584040	6.5	10	4	10
C199584060	6.5	10	6	10
C199584080	6.5	10	8	10

4 1/4" MANDREL SIZE

C199584220	8.0	12	2	10
C199584240	8.0	12	4	10
C199584260	8.0	12	6	10
C199584280	8.0	12	8	10

REINFORCED ANTI-SPARK POLYURETHANE HOSE

FEATURES

- Spark & scorch resistant
- Excellent resistance to oils, solvents & other non-aqueous solutions
- Long service life with outstanding ageing qualities
- Light & flexible
- High impact strength, as well as high tensile & tear strength

SPECIFICATIONS

Temperature range	-30°C to +60°C
Construction	Ester based polyurethane reinforced with polyester fibre.



ANTI-SPARK 50 METRE COILS



285

PART NUMBER



C199581230	8.0	12.0	14
C199581330	9.5	13.5	12
C199581637	11.0	16.0	12

Do you also need?



Quick connect pneumatic couplings



Find it on pages 7 – 21, section one