

REINFORCED POLYURETHANE HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Chemicals Fuel / oil Gases, liquids & solvents 	<ul style="list-style-type: none"> Exceptional abrasion resistance Resistant to a wide range of chemicals High flexibility Colour – crystal clear
SPECIFICATIONS	
Temperature range	-30°C to +70°C
Pressure rating	Values given are based on the short term burst pressure of PCPR hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Crystal clear reinforced ether polyurethane.

Supplied in full coils only



WRAS approved for the conveyance of water up to 23°C



PCPR – CLEAR 30 METRE COILS

1140

PART NUMBER				
PCPR 06	6.3	1/4	12	10.0
PCPR 10	10.0	3/8	16	8.0
PCPR 12	12.5	1/2	19	5.0
PCPR 19	19.0	3/4	26	4.5
PCPR 25	25.0	1	34	2.5

UNREINFORCED POLYURETHANE TUBE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Chemicals Fuel 	<ul style="list-style-type: none"> Outstanding abrasion resistance Raw materials used are acceptable under FDA regulations 175.105, 177.1680, 177.2600 Lightweight & extremely flexible – even at low temperatures Highly elastic
SPECIFICATIONS	
Temperature range	-30°C to +70°C
Construction	100% ether polyurethane.

Supplied in full coils only

NOTE

Unreinforced polyurethane is not recommended for pressure applications



WRAS approved for the conveyance of water up to 23°C



PU – CLEAR 30 METRE COILS

1140

PART NUMBER			
PU3/6	3	1/8	6
PU5/8	5	3/16	8
PU6/9	6	1/4	9
PU6/12	6	1/4	12
PU8/11	8	5/16	11
PU8/14	8	5/16	14
PU10/16	10	3/8	16
PU13/19	13	1/2	19

Do you also need?

PARKAIR®

Brass adaptors

AIGNEP

CAMOZZI
Automation



Find it on pages 548 – 568, section nine